

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.	30-025-34899
5. Indicate Type of Lease	STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.	VO-4510
7. Lease Name or Unit Agreement Name	
Sand Springs ASU State	
8. Well No.	4
9. Pool name or Wildcat	Sand Springs Devonian
10. Elevation (Show whether DF, RKB, RT, GR, etc.)	
4146' GR	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER	2. Name of Operator YATES PETROLEUM CORPORATION
3. Address of Operator 105 South 4th St., Artesia, NM 88210	4. Well Location Unit Letter B : 700 Feet From The North Line and 1650 Feet From The East Line Section 11 Township 11S Range 34E NMPM Lea County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 4146' GR	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: Spud, conductor, resume drilling, surface casing & cement <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 26" hole with rat hole machine at 2:30 PM 2-3-2000. Drilling to 40'. Set 40' of 20" conductor pipe. Cemented to surface. NOTE: Notified Sylvia w/OCD-Hobbs of intent to spud. Resumed drilling a 17-1/2" hole with rotary tools at 12:00 PM 2-8-2000.

TD 434'. Reached TD at 5:15 PM 2-8-2000. Ran 10 joints of 13-3/8" 48# H-40 (450.17') of casing set at 434'. 1-Texas Pattern notched guide shoe set at 434'. Insert float set at 405'. Cemented with 425 sacks Premium Plus and 2% CaCl2 (yield 1.34, weight 14.8). PD 11:35 PM 2-8-2000. Bumped plug to 450 psi, OK. Circulated 91 sacks cement. WOC. Cut off and welded on flow nipple. Tested BOP to 500 psi. Drilled out at 12:30 PM 2-9-2000. WOC 24 hours and 55 minutes. Reduced hole to 12-1/4". Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Operations Technician DATE March 24, 2000
TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-1471

(This space for State Use)

APPROVED BY

TITLE Geologist

DATE

CONDITIONS OF APPROVAL, IF ANY: