

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1530, Hobbs, NM 88240

DISTRICT II
P.O. Drawer 90, Artesia, NM 88210

DISTRICT III
1800 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.

30-025-35148

5. Indicate Type of Lease

STATE ☒

FEE ☐

6. State Oil & Gas Lease No.

VA-1333

7. Lease Name or Unit Agreement Name

Taco AUK State

8. Well No.

2

9. Pool name or Wildcat

Wildcat Devonian

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☒

GAS
WELL ☐

OTHER

2. Name of Operator

YATES PETROLEUM CORPORATION

3. Address of Operator

105 South 4th St., Artesia, NM 88210

4. Well Location

Unit Letter A : 660 Feet From The North Line and 660 Feet From The East Line

Section

10

Township

10S

Range

34E

NMPM

Lea

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

4197' GR

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: Intermediate casing & cement ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 4141'. Reached TD at 1:00 PM 9-12-2000. Ran 100 joints of 8-5/8" 32# J-44 ST&C (4147.42') of casing set at 4141'. 1-Texas Pattern notched guide shoe set at 4141'. Float collar set at 4097'. Cemented with 750 sacks Interfill C and 1/4#/sack flocele (yield 2.46, weight 11.9). Tailed in with 250 sacks "C" with 2% CaCl2 (yield 1.34, weight 14.8). PD 6:15 AM 9-13-2000. Bumped plug to 1500 psi, OK. Circulated 115 sacks. WOC. Nipped up and tested to 5000 psi for 10 minutes, OK. Drilled out at 9:15 AM 9-14-2000. WOC 27 hours. Reduced hole to 7-7/8". Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Rusty Klein

TITLE

Operations Technician

DATE Feb. 15, 2001

TYPE OR PRINT NAME

Rusty Klein

TELEPHONE NO. 505/748-1471

(This space for State Use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: