

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.
30-025-35148

5. Indicate Type of Lease
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.
VA-1333

7. Lease Name or Unit Agreement Name

Taco AUK State

8. Well No.
2

9. Pool name or Wildcat
Wildcat Devonian

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. Name of Operator
YATES PETROLEUM CORPORATION

3. Address of Operator
105 South 4th St., Artesia, NM 88210

4. Well Location
Unit Letter A : 660 Feet From The North Line and 660 Feet From The East Line
Section 10 Township 10S Range 34E NMPM Lea County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
4197' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: Spud, conductor, resume drilling, surface casing & cement ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 20" hole with rat hole machine at 10:30 AM 9-4-2000. Drilled to 40'. Set 40' of 16" conductor pipe. Cemented to surface. NOTE: Notified Sylvia w/OCD-Hobbs via voice mail. Resumed drilling a 14-3/4" hole with rotary tools at 12:00 PM 9-6-2000.

TD 400'. Reached TD at 6:00 PM 9-6-2000. Ran 10 joints of 11-3/4" 42# H-40 ST&C (404.77') of casing set at 400'. 1-Texas Pattern notched guide shoe set at 400'. Insert float set at 366'. Cemented with 350 sacks Class C with 2% CaCl2 (yield 1.34, weight 14.8). PD 11:15 PM 9-6-2000. Bumped plug to 500 psi, OK. Circulated 25 sacks. WOC. Cut off and welded on flow nipple. Drilled out at 6:00 PM 9-7-2000. WOC 18 hours and 45 minutes. Reduced hole to 11". Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Operations Technician DATE Feb. 15, 2001

TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-1471

(This space for State Use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: