

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLY
(Other instruction:
reverse side)Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐		5. LEASE DESIGNATION AND SERIAL NO. 057004
2. NAME OF OPERATOR Sam Boren		6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR Box 953, Midland, Texas		7. UNIT AGREEMENT NAME J
4. LOCATION OF WELL (Report location clearly and in accordance with any State laws. See also space 17 below.) At surface 1980 S 1980 E Section 33		8. FARM OR LEASE NAME Trans-Mountain Federal
14. PERMIT NO.		9. WELL NO. 1
15. ELEVATIONS (Show whether DF, RT, GR, etc.) GL 4014		10. FIELD AND POOL, OR WILDCAT Allison Penn
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 33 8S 37E
		12. COUNTY OR PARISH Roosevelt
		13. STATE New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF	☐	PULL OR ALTER CASING	☐
FRACTURE TREAT	☐	MULTIPLE COMPLETE	☐
SHOOT OR ACIDIZE	☐	ABANDON*	☐
REPAIR WELL	☐	CHANGE PLANS	☐
(Other)	☐		

SUBSEQUENT REPORT OF:

WATER SHUT-OFF	☐	REPAIRING WELL	☐
FRACTURE TREATMENT	☐	ALTERING CASING	☐
SHOOTING OR ACIDIZING	☐	ABANDONMENT*	☒
(Other)	☐		

(NOTE: Report Results of multiple completion or Well Completion or Recombination Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Well plugged as follows:

25 sax pumped down 4 1/2" csg. to 9500'; 4 1/2" csg. show @ 4929', pumped in 25 sax down 4 1/2" csg. 7 5/8 shoe @ 4270, pumped 25 sax down 4 1/2" csg. @ 4295; 7 5/8" csg. shot @ 1347, pumped 25 sax down 7 5/8" csg. 10 3/4 shoe @ 442', pumped 25 sax down 7 5/8" csg. @ 465; 10 sax in top of 10 3/4" csg.

Steel marker erected. Will notify when ready for inspection.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Agent

DATE

3/17/66

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

APPROVED

APR 1 1966

*See Instructions on Reverse Side

J. L. GORDON
ACTING DISTRICT ENGINEER

X68 25
"8\1
X62