

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPlicate
(Other instructions
verse side)Form approved
Budget Bureau No. 43-21494

5. LEASE DESIGNATION AND SERIAL NO.

N.M. 9523202

6. IF OTHER, ALLOTMENT OR OTHER NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal N. M. #3

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

South Prairie Atoka Gas

11. SEC., T., R., M., OR S.W. 1/4
SECTION OR AREA

Sec. 29, T-8-S, R-36-E

12. COUNTY OR PARISH OR STATE

Roosevelt New Mexico

1. OIL ☐ GAS ☒ OTHER ☐

2. NAME OF OPERATOR

Lone Star Producing Company

3. ADDRESS OF OPERATOR

Box 4815, Midland, Texas 79702

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)At surface
660' from North Line & 660' from East Line of Section 29,
T-8-S, R-36-E, Roosevelt County, New Mexico

14. PERMIT NO.

Approved 10-2-64

15. ELEVATIONS (Show whether DF, ST, GR, etc.)

Ground 4,116.5'

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Set Whip Stock

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and space perti-
nent to this work.)*

Cleaned out with 7-7/8" bit to top of junk at 7,574' by drill pipe measurements.
Ram Guns ran Caliper Survey from 7,574' up to 6,574'. Laid whip stock plug from 7,574'
up to 7,309'. Plug was 85 sacks Lone Star regular cement with 15% 20/40 mesh frac sand
added. Ran Sperry-Sun Directional Survey from surface to 7,309'. Hole displacement
85.56', 14.73' South, 84.2' West or 8° South and 5 minutes West of true vertical.
Drilled cement plug from 7,309' to 7,422' with 7-7/8" bit. Set whip stock South, 40°
West at 7,422'. Drilling 7-7/8" hole below whip stock at 7,454', 34° South, 22 West.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Dist. Prod. Supt.

DATE Nov. 19, 1964

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: