

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐

2. NAME OF OPERATOR

American Petrofina Co. of TX

3. ADDRESS OF OPERATOR

Box 1311, Big Spring, TX 79720

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: **1980' FS & WL, Sec. 20, T-8-S,**
AT TOP PROD. INTERVAL: **R-36-E**
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

☐
☐
☐
☐
☐
☐
☐
☒

5. LEASE

NM 051845-B

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal "E"

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

Prarie Cisco South

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 20, T-8-S, R-36-E

12. COUNTY OR PARISH

Roosevelt

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
4135 DF

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

RECEIVED

MAR 03 1981

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1-15 to 1-23-81

Set CIBP at 9650' in 4-1/2" casing with 50' cement on top.

Set CIBP at 8390' in 4-1/2" casing with 50' cement on top.

Cut 4-1/2" casing at 5000' and at 4200'. Pulled 4200' of 4-1/2" casing.

Spotted 50' of cement in and out of 4-1/2" casing stub using mud laden fluid to spot.

Spotted 50' of cement in and out of 8-5/8" casing shoe.

Set 10 sx cement plug at surface and set 4" pipe marker.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED **J. C. Chapman** TITLE **Asst. Dist. Mgr. of Prod.** DATE **March 2, 1981**

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: **Approved as to plugging of the well bore. Liability under bond is retained until surface restoration is completed.**

*See Instructions on Reverse Side

APPROVED
PETER W. CHESTER

FEB 9 1987

BUREAU OF LAND MANAGEMENT
ROSWELL RESOURCE AREA