

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions reverse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 02915

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐		7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR AMERICAN PETROFINA COMPANY OF TEXAS		8. FARM OR LEASE NAME Federal "F"
3. ADDRESS OF OPERATOR Box 1311, Big Spring, Texas 79720		9. WELL NO. 1
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 660' FNNWL Section 21, T-3-S, R-36-E NMPM		10. FIELD AND POOL, OR WILDCAT Meririe San Andres, South 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 21-8S-36E NMPM
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 4142 DF	12. COUNTY OR PARISH Roosevelt
		13. STATE New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐**Recompletion in San Andres** ☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

12-10-71 - Set a cast iron bridge plug @ 9550 and dumped 18' cement on top.
Perforated 4-1/2" casing 4 holes for squeeze at 5100' and cemented w/
200 Sx. Class C 50/50 Pozmix cement.

12-11-71 - Perforated 4-1/2" casing w/ 4 holes @ 4800' and cemented through perfs.
with 100 Sx. Class C 50/50 Pozmix cement.

12-13-71 - Drilled out cement in casing @ PRTD 5064.

12-14-71 - Perforated 4-1/2" csg for production at 4846, 4860, 4893, 4900, 4901, 4909,
4911, 4913, 4931, 4934, 4941, 4968, 4971, 4974 & 4975 (15 holes). Acidized
with 6000 gals. NE 20% acid in 4 stages using benzoic acid as diverting
agent between stages.

18. I hereby certify that the foregoing is true and correct

SIGNED

R.C. BottTITLE **Asst. Dist. Mgr. of Prod.**DATE **1-11-72**

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

ACCEPTED FOR RECORD

JAN 14 1972

*See Instructions on Reverse Side

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1963-O-685229

687-831

RECEIVED

JAN 1 1964

U.S. DEPARTMENT OF THE INTERIOR

BUREAU OF LAND MANAGEMENT