

*NM OCA*  
*Hoflo*

~~NOT FOR PUBLIC USE~~

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well ☐ gas well ☐ other

2. NAME OF OPERATOR  
American Petrofina Co. of TX

3. ADDRESS OF OPERATOR  
Box 1311, Big Spring, TX 79720

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1980 FNL, 1980 FWL, Sec. 20  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☒

**RECEIVED**  
FEB 1 1982

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

5. LEASE  
NM 002915

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Federal "C"

9. WELL NO.  
1

10. FIELD OR WILDCAT NAME  
Prarie South Wolfcamp

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 20, T-8-S, R-36-E

12. COUNTY OR PARISH  
Roosevelt

13. STATE  
N.M.

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
4124 DF

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

6-10-81 Pumped in 100 bbls. 9.5# brine. Set CIBP at 8950 with 45 ft. cement on top.

6-12-81 Cut 5 1/2" casing at 5490' but could not pull. Cut 5 1/2" casing at 4952' and pulled out of hole.

6-16-81 Spotted 40 sx cement from 5000' to 4860'. Spotted 40 sx cement from 4265' to 4132'.

6-17-81 Set 10 sk cement plug at surface & set 4 1/2" pipe marker. Well site now ready for inspection.

*Contacted J.C. Chapman. He said that the 100' cement plug, across from 13 3/8" shoe, inside 8 5/8" casing was not installed. I accepted the program minus this plug because the 8 5/8" had cement to surface. Peter W. Chalk*

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED J.C. Chapman TITLE Asst. Dist. Mgr. of Production DATE February 1, 1982

(This space for Federal or State office use)

APPROVED BY Peter W. Chalk TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY:

NOV 5 1982  
FOR  
JAMES A. GILHAM  
DISTRICT SUPERVISOR

See Instructions on Reverse Side