

RECEIVED
COMMISSION
OCT 31 1951
OIL CONSERVATION COMMISSION
HOBBS-OFFICE

Santa Fe, New Mexico

WELL RECORD

AREA 640 ACRES
LOCATE WELL CORRECTLY

Paul L. Davis

Statistik

Company or Operator

Lease

Well No. 1 in SE1/4SE of Sec. 32, T. 7S

R. 38E, N. M. P. M., Wildest Field, Roosevelt County.

Well is 660 feet south of the North line and 660 feet west of the East line of SE 1/4 SE 1/4

If State land the oil and gas lease is No. E-2415 Assignment No. Not available

If patented land the owner is _____, Address.

If Government land the permittee is _____, Address _____

The Lessee is Paul L. Davis Box 271, Address Midland, Texas

Drilling commenced 9-23 1951. Drilling was completed 10-27 1951.

Name of drilling contractor Donnell Drilling Company, Address Odessa, Texas

Elevation above sea level at top of casing 3993 feet.

The information given is to be kept confidential until _____ 19

OIL SANDS OR ZONES

No. 1, from _____ to _____ No. 4, from _____ to _____

No. 2, from _____ to _____ No. 5, from _____ to _____

No. 3, from _____ to _____ No. 6, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from bone encountered to _____ feet.

No. 2, from _____ to _____ feet. _____

No. 3, from _____ to _____ feet. _____

No. 4, from _____ to _____ feet. _____

CASING RECORD

[illegible]

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
11 1/2	8 5/8"	312	225	Plug		
7 7/8	5 1/2"	4750	150	Plug		

PLUGS AND ADAPTERS

Heaving plug—Material_____Length_____Depth Set_____

Adapters—Material _____ Size _____

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	STAINLY USED	15-76400-1 CHEMICAL USED	QUANTITY	DATE	DEPTH 366 6 TREATED	DEPTH CLEANED OUT
------	--------------	-----------------------------	----------	------	-----------------------------------	-------------------

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
•	312	312	Sand & shale. Set 8 5/8" csg. @ 312. 15 jtn. 225 sacks cement.
312	612	300	Redbed
612	1700	1088	Redbed & shells
1700	1925	225	Redbed & blue shale
1925	2070	145	Redbeds & shells
2070	2320	250	Redbeds & streaks of anhydrite
2320	2460	140	Ashy & salt
2460	2790	330	Salt & ash
2790	2845	55	Ashy & shale
2845	3312	567	Ashy & salt
3312	3703	381	Ashy & shale
3703	3788	85	Ashy
3788	3860	72	Ashy & shale
3860	4203	343	Ashy & lime
4203	4807	604	Lime - 9 1/2" csg. set @ 4750' with 150 sacks cement.
4807	4841	34	Lime