Meene entre rue

The expected mud program will estail use of plain water and native mud to 13-3/8 inch casing point at or about 400 feet, brine water from the parface string casing point at or about 400 feet to the intermediate string casing point at or about 4, 250 feet, plain water and native mud from intermediate string casing point at or about 4, 250 feet to approximately 8, 500 feet and oil base mud with weights and viscosities as needed to maintain satisfactory hole condition from 8, 500 feet to total depth.

Surface casing, 13-3/8 inch, will be circulated with cement back to the surface. Intermediate casing, 8-5/8 inch, will be circulated with cement back to the surface string. Oil string casing, 5-1/2inch, will be cemented with approximately 560 sacks.

Signed for Identification:

DAVID FASKEN

By Richard & Brooks - Attorney

the augusta company program will notall use of plate water and mative models (3+3/3 tack second to some at an about stif sector water them the particle structure of the star about to need to about stif readiate string casting points at or about of 200 feet, put water and act or a structure to are distore and the casting point as at a bound of 200 feet, put water difference to a tructure distore and the casting point of a structure of the structure and act or a structure to a structure distore and the point of a structure of the structure difference to a structure of the structure of the structure of the structure of the structure and act or a structure of the structure of the structure of the structure of the structure difference to a structure of the structure structure of the structure structure of the struct

വിരം പറ്റും പാര്യം പ്രദിനായമായം അവിവേഷം ബ്രോജ്ജിലെ നില്ലാം പോലായായം പായിര്യം പോര്ഷ്ണം പോര്ഷ്ണം കോന് മേഷംഗേഷം അതിക്കുന്നത്തിന്റെ പോര്⁶8 മോയത്ത് നില്ലെന്റും നില്ലോൾ അദ്ധാനമയ കണ്ടായ്മായില്ലോ വായക്കാ**ക് താലലുളം** നി നില്ലാം മംഗംഗം കര്ത്തിന് നില്ലാനിയ നില്ലാ നില്ലാൻ തുടന്നും പെട്ടാം പുളന്നും പോനായും പ്രോജിയി കലാലിലോം.

Richard Onling