Santa Pa

Form	9-8318
(Feb	. 1951)

(SUBMIT IN TRIPLICATE)

## UNITED STATES

Land Office	a			
Lease No	LC	060	742	<b>-</b> B

## **GEOLOGICAL SURVEY**

DEPARTMENT OF THE INTERIOR

## SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	 SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS.		
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	 SUBSEQUENT REPORT OF ALTERING CASING.	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	 SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	 SUBSEQUENT REPORT OF ABANDONMENT	<b>*</b> '
NOTICE OF INTENTION TO PULL OR ALTER CASING	 SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL.	 	
		-

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

January 16 Peatherstone Well No. 11 is located 660 ft. from S line and 1930 ft. from E line of sec. 30 SW/48E/4 30 South 36East (Twp.) (Range) (Meridian) Rossevelt New Yexico (County or Subdivision) (Field) (State or Territory)

The elevation of the derrick floor above sea level is 4135 ft.

## DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work) Spudded: 11-12-62 TD: 11-28-62, 4871\* Surface Pipe: 362' of 8-5/8"-Cement Circulated Hole Size: 7-7/8" from 362'to 4820'. 6-1/8" from 4820' to 4871' 1. 4871" - 4771" 100 Cement Plug 2. 2850' - 2750' 100 Cement Plug 32 sacks cement 3. 220**6'** - 2100' 100 Cement Flug 32 sacks coment 375' - 325' 50 Cement Plug 5. Set & comented 4-1/2" marker pipe 4' above surface. Location cleaned up and ready for inspection.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company	Clan F. Featherstone	
Address	236 Petroleum Building	
	Rosvell, New Mexico	By Charles W. J Liels
		Charles W. Sicks Title General Manager