Form 3160-5 December 1989) P. C. BC.

HOBBS, MEW MEXICO 88240

. a a salaisii .

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED Budget Bureau No. 1004-0135 Expires: September 30, 1990

5 Lease Designation and Serial No.

LC-060978

SUNDRY NOTICES AND REPORTS ON WELLS

ne and use this form for proposals to dr	AND REPORTS ON WELLS ill or to deepen or reentry to a different reservoir. R PERMIT—" for such proposals	6 If Indian, Allottee or Tribe Name 7 If Unit or CA, Agreement Designation
SUBMIT IN TRIPLICATE		
Type of Well A Oil Well Gas Well Other 2. Name of Operator XERIC OIL & GAS COMPANY 3. Address and Telephone No P.O. BOX 51311, MIDLAND, T 4. Location of Well (Footage, Sec., T., R., M., or Survey D 1980FNL, 1980FEL, S14, T8S		MILNESAND (UNIT) 8. Well Name and No. 172 9. API Well No. 36-04/-00119 10. Field and Pool, or Exploratory Area MILNESAND (SAN ANDRES 11. County or Parish, State ROOSEVELT
12 CHECK APPROPRIATE BOX	(s) TO INDICATE NATURE OF NOTICE, REPO	RT, OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF ACTION	
X Notice of Intent Subsequent Report	Anandonment Recompletion Plugging Back Casing Repair	Change of Plans New Construction Non-Routine Fracturing Water Shut-Off
Final Abandonment Notice	Altering Casing Altering Casing Mechanical Note Report results Recompletion Report all pertinent details, and give portinent tates including estimated date of starti	Conversion to Injection Integrity Test of multiple completion on Well Completion or and Log form.) ng any proposed work. If well is directionally drilled
	all pertinent details, and give pertinent are to change details work incal depths for all markers and renes pertinent to this work. Set or will be set. Well will be set.	be pressure tested

for mechanical integrity to 500psi for 30 minutes. BLM will be notified in advance in order to witness test, if desired.

14 I hereby certify 10-29-92 APPROVED PETER W. CHESTER nt statements Title 18 U.S.C. Section 1001 makes it a crime for any person knowing's and willing BUREAU GF LAND MANAGEMENT ir representations as to any nutrier within its jurisdiction ROSWELL RESOURCE AREA *See Instruction on Reverse Side

Additional Stipulations for Casing Integrity Test

- 1. The cast iron bridge plug shall be set within 100 ft. of the upper most perforations or casing shoe if completed open hole.
- 2. Also notify the New Mexico Oil Conservation Division (NMOCD) prior to test.