Form 3160-5 (December 1989)

## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED Budget Bureau No. 1004-0135 Expires: September 30, 1990

5. Lease Designation and Serial No.

LC-060978 6 If Indian, Allottee or Tribe Name

## SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals 7 If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE MILNESAND (SA) UNIT 1. Type of Well 8. Well Name and No Oil Gas Well Well Other 173 2. Name of Operator 9. API Well No. XERIC OIL & GAS COMPANY 30-041-00170 3. Address and Telephone No. 10 Field and Pool, or Exploratory Area 79710 (915)683-3171 P.O. BOX 51311, MIDLAND, TEXAS MILNESAND (SAN ANDRES 4 Location of Well (Footage, Sec., T., R., M., or Survey Description) 11 County or Parish, State Roosevelt 660FNL,660FEL,S14,T8S,R34E CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF ACTION TYPE OF SUBMISSION Change of Plans X Notice of Intent **New Construction** Recumpletion Non-Routine Fracturing Plugging Back Subsequent Report Water Shut-Off Casing Repair Conversion to Injection Altering Casing Final Abandonment Notice Mechanical Integrity Test (Note Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 13 Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent lates) including estimated date of starting any proposed work. If well is directionally drifted give subsurface locations and measured and true vertical depths for all markers are a perspective this work. Well will be pressure tested

Cast iron bridge plug is set or will be set. for mechanical integrity to 500psi for 30 minutes. BLM will be notified in advance in order to witness test, if desired.

14 | hereby certi 10-29-92 (This space for PETER N. CHESTER BUREAG OF LAND MANAGEMEN fictimous or fraudule statement Title 18 U.S.C. Section 1001 makes it a crime for any person knowingly or representations as to any matter within its jurisdiction ROSWETT RESOURCE AREA \*See Instruction on Reverse Side

## Additional Stipulations for Casing Integrity Test

- 1. The cast iron bridge plug shall be set within 100 ft. of the upper most perforations or casing shoe if completed open hole.
- 2. Also notify the New Mexico Oil Conservation Division (NMOCD) prior to test.