ACTING DISTRICT ENG SUNDRY NO NOTICE OF INTENTION TO DRILL NOTICE OF INTENTION TO CHANGE PLANS	GEPARTMENT OF THE INTERIOR SINEER GEOLOGICAL SURVEY OTICES AND REPORTS SUBSEQUENT REPORT OF SUBSEQUENT SUBSEQUENT REPORT OF SUBSEQUENT SUBSEQ	ON WELLS VATER SHUT-OFF
NOTICE OF INTENTION TO TEST WATER S		LTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR F		BANDONMENT
NOTICE OF INTENTION TO SHOOT OR ACT	CUIDDI EMENTARY WELL HIS	STORY
NOTICE OF INTENTION TO PULL OR ALIE NOTICE OF INTENTION TO ABANDON WELL	Them A Sank 1	J. Liner I
		ft. from \(\begin{array}{c} arra
	7-A-S B-36-E NOM	,
W. 2 of Section 21	(Twp.) (Range) (Merid	lian)
meth Preirie Penn	(County or Subdivision)	(State or Territory)
The elevation of the derrick fl	DETAILS OF WORK	and casings, indicate mudding jobs, come
State names of and expected depths to ob-	bjective sands; show sizes, weights, and lengths of prop ing points, and all other important proposed work))
Lone Ster Fredneing Comparing Compar	piective sands; show sizes, weights, and lengths of proping points, and all other important proposed work) pany - Federal N. N. "B" No. 1 2,769' to 13,139'. Flugged to the E.U.E. 9.30f R-80 (table) Generated with 175 seeks 505 in the Seeks 5	Well mark to 12,263'. Mg) liner set at 12,300' Pennix and Lame Ster Inc with 2500' water pressu ind 35° liner by Tempera rebber packing.
Drilled 6-1/h" hele from the and set 16" 0.D. See Top of liner at 9,176'. consett. Tosted 7" configuration. No pro- Survey is 10,180'. Top	pany - Federal N. H. "P" No. 1 2,769' to 13,139'. Plugged to the E.U.E. 9.30f H-50 (table Generated with 175 seeks 205 in the sector lose. Top of cament behind a limer smaled with load and must receive approval in writing by the Geological Surpretucing Company	well mark to 12,263'. Iner set at 12,300' Pennix and Less Ster Ine with 2500' water pressu ind 35' liner by Tempera rebter packing.
Drilled 6-1/h" hele from the and set 16" O.D. See Top of liner at 9,476'. consett. Tosted 7" cash for 30 minutes. No gree Survey is 18,480'. Top I understand that this plan of work. Company Lene Star From Address Box 1815	pany - Federal N. H. "P" No. 1 2,769' to 13,139'. Plugged to the E.U.R. 9.30f N-60 (tubes Gos 10, 175 seeks 505 in the 175 seeks 505 i	well make to 12,263'. Increate at 12,300'. Possix and Lose Star Inc. with 2500' water pressuring Jimer by Tomperar rebber packing.
Prilled 6-1/h" hele from the and set 30 0.D. See top of liner at 9,476. senset. Tosted 7" cash for 30 minutes. No pro-bury is 10,460. Top	pany - Federal N. M. "B" No. 1 9,769' to 13,139'. Flugged to the E.U.E. 9.305 R-60 (tubes God to the Long to tubes God to the Long to the Source loss. Top of coment book of liner scaled with load and must receive approval in writing by the Geological Surreducing Company By	well pack to 12,263'. In liner set at 12,300' Posmix and Lose Star Inc with 2500' water present ind 36' liner by Tempera rebter packing.