

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPI
(Other instructions
verse side)

TE*
re-

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

44-073669

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Lone Star Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat (South Prairie)

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

20-8S-36E

12. COUNTY OR PARISH

Roosevelt

13. STATE

New Mexico

1.

OIL ☒ GAS ☐
WELL WELL OTHER

2. NAME OF OPERATOR

J.M. Huber Corporation

3. ADDRESS OF OPERATOR

1900 Wilco Building, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

**At surface
660' FW&L of Section 20, T-8-S, R-36-E**

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4121.4' GR

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☒

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

MIRURT 6/5/1968.

Squeezed old San Andres perforations 4884-4906 and 4927-4935 w/75 sx Incon Class "C", 1 1/2 D-59, 5 1/2 NaCl at 1800 PSI. Job completed 5:00 A.M. 6/6/1968. Drilled cement and cleaned out to 9675'. Pressure tested 7" casing to 2000 PSI, held OK. Started drilling under 7" casing w/6-1/8" bit at 3:30 A.M. 6/10/1968. Drilled to RTD 13,000' at 2:00 P.M. 8/17/68. Ran 4-1/2", 11.60#, N-80, LT&C liner set at 13,000'. Top liner at 9299'. Cemented liner w/500 sx Class "H" with .2 1/2 D-13 and 1 1/2 DSG. Plug down at 5:50 A.M. 8/22/68. Reversed out 50 sx cement off top liner. WOC 5 days. Pressure tested 7" casing, and 4-1/2" liner to 2000 PSI, held OK. Prep to perforate Devonian 12,871' - 12,947'.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

District Production Supt.

DATE

8/27/1968

(This space for Federal or State office use)

APPROVED BY

TITLE

APPROVED

CONDITIONS OF APPROVAL, IF ANY:

AUG 28 1968

*See Instructions on Reverse Side

**J L GORDON
ACTING DISTRICT ENGINEER**

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.