Form 9–331 Dec. 1973 UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different		Form Approved. Budget Bureau No. 42–R1424	
		5. LEASE NM-058677 Å	
		6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
		7. UNIT AGREEMENT NAME	
reservoir. Use Form 9–331–C for such proposals.)	plug back to a different	8. FARM OR LEASE NAME	
1. oil XX gas other		9. WELL NO.	ederal B
2. NAME OF OPERATOR			3
SNB Operating Co.		10. FIELD OR WILDCAT NAI	
3. ADDRESS OF OPERATOR P.O. Box 543 Lovington N M 88260		South Prair 11. SEC., T., R., M., OR BL	
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17		ARESec. 31 T 2	
			35. 36E
AT SURFACE: 660/N 1980/	α	12. COUNTY OR PARISH	3. STATE
AT TOP PROD. INTERVAL: AT TOTAL DEPTH:		Roosevell NM	
16. CHECK APPROPRIATE BOX TO INDICATE N		14. API NO.	
REPORT, OR OTHER DATA	· 1—	15. ELEVATIONS (SHOW D	OF, KDB, AND WD)
		4107 (•
	NT REPORT OF:		
TEST WATER SHUT-OFF			
SHOOT OR ACIDIZE			
REPAIR WELL PULL OR ALTER CASING		(NOTE: Report results of multi change on Form 9–33	
MULTIPLE COMPLETE		change on rollings-00	
CHANGE ZONES		7	温品 而
ABANDON* (other)		•	A A
	-		F 0 Z
17. DESCRIBE PROPOSED OR COMPLETED OPE including estimated date of starting any prop	osed work. If well is dire	ectionally drilled, give subst	ive pertinent dates, the pertinent dates dates, the pertinent dates dates, the pertinent dates date
measured and true vertical depths for all mark 133/8-417'-400sxs	ers and zones pertinent t Perforations	to this work.)*	0 3
8 5/8-4333'-1781sxs	8992'-9004'	,	
5 1/2-9227' - toc cal 3700' 9756'	9676-9715	,	m
1. CIBP @ 9600'-dump 35'cement o	n top		
2. Circulate hole with 10# mud		5 1 /O	
 cut and pull from freepoint a Spot 100' cement in and out o 		e 5 1/2 casing	
5. Spot 50 sxs cement in and out 5			
6. Cut and pull any 9 5/8 casing	if free belie	eve to be circul	Lated
7. Spot 100' cement in and out o	f stub if pul	lled	
8. Spot 85 sxs @ 467'-367'	= d'amit = 0	2	
9. Spot 10 sxs e surface minim	um 50 Arai pa	eg .	
Install dry hole ma	rker	Set @) Ft.
18. I hereby certify that the foregoing is true and c	orrect		
SIGNED Auth	E Agent	DATE	-90
(This sp.	ce for Federal or State office	e use) ! AP	PROVED
APPROVED BYTI	TLE	DETER	W. CHESTER
CONDITIONS OF APPROVAL, IF ANY:			
Edditional plug; 170'cmt. plug 7470'-7300'		j FEB	2 8 1990
	Instructions on Reverse Sig	BUREAU OF L ROSWELL	AND MANAGEMENT RESOURCE AREA

RECEIVED

MAR 2 1990

OCD Hobes offi**ce**