xSubmit 3 Copies To Appropriate District Office	State of New Mexico			Form C-103
District I 1625 N. French Dr., Hobbs, NM 88240	Lnergy, Minerals and Natural Resources		Revised March 25, 1999 WELL API NO.	
District II	OIL CONSERVATION DIVISION		30-041-00139	
811 South First, Artesia, NM 88210 <u>District III</u>	2040 South Pacheco		5. Indicate Type	
1000 Rio Brazos Rd., Aztec, NM 87410 District IV	Santa Fe, NM 87505		STATE [6. State Oil & C	FEE X
2040 South Pacheco, Santa Fe, NM 87505			o. State on &	aus Leuse 140.
SUNDRY NOTICES (DO NOT USE THIS FORM FOR PROPOSALS) DIFFERENT RESERVOIR. USE "APPLICATI PROPOSALS.) 1. Type of Well: Oil Well Gas Well		JG BACK TO A	7. Lease Name of MILNESAND UI	r Unit Agreement Name: NIT
2. Name of Operator	Olici Hyberion		8. Well No.	196
J. CLEO THOMPSON				
3. Address of Operator 325 N. ST. PAUL, SUITE 4300, DALLAS, TX 75201			9. Pool name or Wildcat MILNESAND (SAN ANDRES)	
4. Well Location				
Unit Letter N: 660 feet from the SOUTH line and 1980 feet from the WEST line				
Section 13	Township 8S Rang	ge 34E	NMPM	County ROOSEVELT
10	0. Elevation (Show whether DI 4262' RKB	R, RKB, RT, GR, etc.,)	
4202 RRB				
11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data				
NOTICE OF INTE	NTION TO:	SUBS	SEQUENT RE	PORT OF:
PERFORM REMEDIAL WORK D	PLUG AND ABANDON	REMEDIAL WORK		ALTERING CASING
TEMPORARILY ABANDON C	CHANGE PLANS	COMMENCE DRIL	LING OPNS.	PLUG AND ABANDONMENT
	MULTIPLE COMPLETION	CASING TEST AN CEMENT JOB	D 🗆	
OTHER		OTHER:		
12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.				
1.) RIH WITH 2 3/8 TUBING AND TAG PLUG AT 4617 (SHOULD HAVE BEEN @ 4415') (**)				
2.) SET 7 5/8 CIBP @ 4450'. DUMPED 35' OF CEMENT ON PLUG WITH WIRELINE.				
4.) PULL UP TO 2280' AND CIRCULATE 56 SX OF CLASS "C" NEAT CEMENT.				
5.) PULL UP TO 2000' AND REVERSE CIRCULATE WITH 9.5# SALT MUD.				
6.) PULL TUBING to 489'. 7.) CIRCULATE 25 SX CLASS "C" CEMENT.AT 489'.				
8.) PULL UP TO 250' AND REVERSE CLEAN. POOH. WAIT 2 HOUR AND RIH AND TAG CEMENT PLUG.				
POOH. SET 10 SX	Per JH.	June 21	2001	
I hereby certify that the information above is true and complete to the best of my knowledge and belief.				
SIGNATURE frim Sta	eign TITLE	ENGINEER	DAT	E11-12-2002
Type or print name JIM STEVI	NS Felephone No. (915)366-8886			
(This space for State use)	1):	4 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		
APPPROVED BY	TITLE	g to I make	DE	C 0 5 2002
Conditions of approval, if any:		MET IN NOT OFFI	 Уср	
	Control of the Contro			
			UX /	