

Form 9-331
May 1963)UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 060978

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)1. ☐ OIL WELL ☐ GAS WELL ☐ OTHER Water Injection Well2. NAME OF OPERATOR
UNION TEXAS PETROLEUM CORPORATION3. ADDRESS OF OPERATOR
1300 Wilco Building, Midland, Texas 797014. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surfaceRECEIVED
APR 15 1980U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

7. UNIT AGREEMENT NAME

Milnesand Unit

8. FARM OR LEASE NAME

9. WELL NO.

31

10. FIELD AND POOL, OR WILDCAT

Milnesand (San Andres)

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 18, T-8-S, R-35-E

12. COUNTY OR PARISH 13. STATE

Roosevelt New Mexico

14. PERMIT NO. Unit Letter "L", 1986' FSL & 660' FWL

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4235' DF

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐
REPAIR WELL ☐	CHANGE PLANS ☐
(Other) ☐	

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
(Other) ☒ Repair packer Failure	

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

1. February 19, 1980 - SI Well - Possible tubing or packer leak.
2. March 25, 1980 - MIRUSU - Released Baker Loc-Set packer. Installed BOP. POH w/2 3/8" tbg.
3. March 26, 1980 - Ran 9 5/8" Baker Model C Full bore packer & tbg. Set pkr. @ 4450'. Pressured casing to 1500# w/no leak off.
4. March 27, 1980 - Pressure tested tubing to 5000#. Found one split collar.
5. March 29, 1980- WIH w/9 5/8" Baker Loc-set pkr. and 2 3/8" tbg. Loaded casing w/250 bbls. 2% KCL wtr. Flanged up wellhead. Set packer & pressured up casing to 1000# w/no leaks. RDSU - Resumed injection.

18. I hereby certify that the foregoing is true and correct

SIGNED

Floyd S. Houdyschell

TITLE Prod. Analyst

DATE 4/14/80

(This space for Federal or State office use)

APPROVED FOR RECORD

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

*See Instructions on Reverse Side