

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico

April 30, 1958

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the Murphy-Dyer Drilling Company

(Company or Operator) Davis Well No. 1 in D (Unit)
NW $\frac{1}{4}$ NW $\frac{1}{4}$ of Sec. 8, T. 8 S, R. 34 E NMPM., Wilcox Pool
 (40-acre Subdivision)
Roosevelt County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

Hole has been drilled to total depth of 4606' and found to be dry. Cores were cut from 4502' to 4503' (barrel plugged); 4531' to 4581', and 4581' to 4606'. Recovery was 100% on all cores. A drill stem test was run between straddle packers from depth of 4400' to 4503'. Recovery was 204' of drilling mud. Bottom hole 30 minute shut in pressure was 175#.

We propose to plug the well as follows: Set 25 sacks of cement in 7-7/8" hole on bottom to cover porous section cored; set 15 sacks at 2500'; set 10 sacks at base of 8-5/8" casing at depth of 354 feet. Fill top of 8-5/8" casing with thirty feet of cement and set four inch regulation marker beside 8-5/8" casing; in cement; with top of marker extending four feet above mean ground level.

Cellar and pits will be backfilled and location site will be left in acceptable condition.

Approved W. C. Murphy, 19____
 Except as follows:

Murphy-Dyer Drilling Company
 By Charles P. Miller

Position Agent
 Send Communications regarding well to:

Approved
 OIL CONSERVATION COMMISSION

By E. Fischer
 Title _____

Name W. C. Murphy
 Address Box 207, Midland, Texas.