


JUL 22 1960

COPY TO C.O.C.

HOBBS

Budget Bureau No. 42-R358.4.
Approval expires 12-31-60.



E. W. STANDLEY
DISTRICT ENGINEER

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office **Hobbs, New Mexico**
Lease No. **NM 03431**
Unit **Las Cruces "B"**

JUL 22 1960

SUNDRY NOTICES AND REPORTS ON WELLS

| | | | |
|---|-------------------------------------|---|--|
| NOTICE OF INTENTION TO DRILL..... | <input checked="" type="checkbox"/> | SUBSEQUENT REPORT OF WATER SHUT-OFF..... | |
| NOTICE OF INTENTION TO CHANGE PLANS..... | | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING..... | |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF..... | | SUBSEQUENT REPORT OF ALTERING CASING..... | |
| NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL..... | | SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR..... | |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE..... | | SUBSEQUENT REPORT OF ABANDONMENT..... | |
| NOTICE OF INTENTION TO PULL OR ALTER CASING..... | | SUPPLEMENTARY WELL HISTORY..... | |
| NOTICE OF INTENTION TO ABANDON WELL..... | | | |

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Hobbs, New Mexico **July 22,** 19 **60**
Las Cruces "B"
Well No. **2** is located **660** ft. from **{N}** line and **1960** ft. from **{E}** line of sec. **30**
NW/4 NE/4 Sec. 30 **S-S** **37-E** **N.M.P.M.**
(1/4 Sec. and 1/4 Sec. No.) (Twp.) (Range) (Meridian)
Bluff-Penn. **Roosevelt** **New Mexico**
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

To be drilled with rotary tools from surface to total depth of approximately 9750' in the Pennsylvanian Formation. Casing program to be approximately as follows:

| Size Hole | Size Casing | Approx. Casing Point | Sacks Cement |
|-----------|-------------|----------------------|--------------|
| 17-1/4" | 13-3/8" OD | 360' | 385 |
| 11" | 8-5/8" | 4236' | 1400 |
| 7-7/8" | 5-1/2" | 9750' | 600 |

The Halliburton Process will be used in cementing all casing and cement will be circulated to surface on the 13-3/8" OD casing.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **Skelly Oil Company**

Address **P. O. Box 38**

Hobbs, New Mexico

By
Title **Dist. Supt.**