

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TWO
(Other instructions
verse side)CATE
on fileForm approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 033910

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

McGrail Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Allison-Penn

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 20-8S-37E

12. COUNTY OR PARISH

Roosevelt

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1.

OIL WELL ☒ GAS WELL ☐ OTHER

2. NAME OF OPERATOR

Marathon Oil Company

3. ADDRESS OF OPERATOR

P. O. Box 220, Hobbs, New Mexico

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)
At surface

1980' FNL & 1980' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, OR, etc.)

4051' DF

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

☒(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Set 40 sack cement plug at PBTD 9605' to cover all perforations. Cut 5-1/2" casing off at 5050'. Placed 20 sack cement plug in and out of the 5-1/2" cut off casing. Placed a 40 sack cement plug across the 9-5/8" casing shoe at 4214'. A 10 sack cement plug was placed in the 9-5/8" casing at the surface. Hole was filled with mud. Installed a steel marker as per NMOCC specifications. Well plugged and abandoned 11-11-66.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Acting
Area Supt.

DATE

12-13-66

(This space for Federal or State office use)

APPROVED

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

MAR 2 1967

*See Instructions on Reverse Side
J L GORDON
ACTING DISTRICT ENGINEER