Form 9-331 (May 1963)

UNITED STATES N. M. QUEBCONSIN Characteristics on reDEPARTMENT OF THE INTERIOR BOXE 1980 OF PARTMENT OF THE INTERIOR BOXES O

| OLOLOGICAL BUILT | | | ו כנסכ מאו | |
|---|---|--|---|--|
| SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.) | | | 6. IF INDIAN, ALLOTTER OR TRIBE NAME | |
| 1. OHL ▼ GAS | | | 7. UNIT AGREEMENT NAME | |
| WE'LL WELL 2. NAME OF OPERATOR | OTHER | | 8. FARM OR LEASE WAME | |
| | | | Irex Federal | |
| Petroleum Production Management, Inc. 3. ADMAGES OF OPERATOR | | | 9. WELL NO. | |
| Suite 2 | 200/Sutton Place Bldg. | Wichita, Kansas 67202 | 2 | |
| 4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1980' FNL & 660' FEL Sec. 20, T-8-S, R-37-E | | | 10. FIELD AND POOL, OR WILDCAT | |
| | | | Allison Penn | |
| | | | 11. SEC., T., R., M., OR BLK. AWD SURVEY OR ARMA | |
| | | | Sec. 20, T-8-S, R-37-E | |
| 14. PERMIT NO. | 15. ELEVATIONS (Show wi | hether DF, RT, GR, etc.) | 12. COUNTY OR PARISH 13. STATE | |
| | 4032.4 GR | | Roosevelt N.M. | |
| 16. | Check Appropriate Box To Indi | cate Nature of Notice, Report, | or Other Data | |
| | | | SSEQUENT REPORT OF; | |
| TEST WATER SHUT-O | OFF PULL OR ALTER CASING | WATER SHUT-OFF | REPAIRING WELL | |
| FRACTURE TREAT | MULTIPLE COMPLETE | FRACTURE TREATMENT | ALTERING CASING | |
| SHOOT OR ACIDIZE | ABANDON* X | SHOOTING OR ACIDIZING | ABANDONMENT* | |
| REPAIR WELL | CHANGE PLANS | (Other) | unite of multiple completion on Well | |
| (Other) | | Completion or Rec | sults of multiple completion on Well ompletion Report and Log form.) | |
| proposed work. If nent to this work.) | R COMPLETED OPERATIONS (Clearly state all post well is directionally drilled, give subsurfs | pertinent details, and give pertinent de ace locations and measured and true ve | ates, including estimated date of starting any ertical depths for all markers and zones perti- | |
| | CIBP in 5 1/2" casing at 93 186') and cap with 35' of c | | erforations from 9466' | |
| | hole with salt gel mud. | | | |
| 3. Spot 25 sacks cement through tubing at 7767' to form 200' cement plug across | | | | |
| | perfs from 7663' to 7667'. | | | |
| 4. Salvage 5 1/2" liner from 4079' - 4271'. | | | | |
| 5. Spot 100 sacks cement at 4321' to provide a 213' cement plug from 50' below top of 5 1/2" casing to 35' above the 9 5/8" casing shoe. They plug from 50' below | | | | |
| 6. Spot 50 sacks cement at 2380' to form a 100/20 lug straddling top of salt | | | | |
| secti 7. Spot | | 5/8" casing to form a 5 | in' cement plug at surface | |
| 8. Erect | 8. Erect dry hole marker. Clean and level location. | | | |
| 9. Contact surface owner (Marlin Pate) and makes accept with him on final | | | | |
| dispo | sition of location and roa | id. | | |
| | | | \ | |
| | | 152 | | |
| | | AUG 2 0 1990 | 1 | |
| | | 1 1 1000 | 1 | |
| | | | / | |
| \ \ | | | , | |
| 8. I hereby certify that | the spregoing is true and correct | CL NEW MY | | |
| SIGNED VI | . Larozzotok TITLE | District Engineer | DATE 8-17-90 | |
| (This space for Federal or State office use) | | | APPROVED / | |
| APPROVED BY TITLE | | | PATE W. CHESTIN | |
| CONDITIONS OF AP | PROVAL, IF ANY: | | A 24 1990 | |

*See Instructions on Reverse Side

PERSONAL RESOURCE AREA