

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-11024.

5. LEASE DESIGNATION AND SERIAL NO.

NM 033910

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

McGrail Federal

9. WELL NO.

3

10. FIELD AND POOL, OR WILDCAT

Allison-Penn

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 20-8S-37E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

. DF 4050'

12. COUNTY OR PARISH

Roosevelt

13. STATE

New Mexico

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

X

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

We propose to plug and abandon this well per instructions and approved methods of the United States Geological Survey commencing November 4, 1966.

The proposed plugging procedure is as follows:

PB TD 9549'. A cement retainer at 8400'. Squeeze with 15 sacks cement beneath retainer and leave 10 sacks cap on top of retainer, cut off 5-1/2" casing at approximately 8000', place a 20 sack cement plug in and out of the cut off 5-1/2" casing and a 30 sack cement plug at the top of the Tubb zone, a 30 sack cement plug at the top of the Abo zone, a 30 sack cement plug at the base of the San Andres zone, and a 40 sack cement plug across the 9-5/8" shoe at 4208'. A 20 sack cement plug will be placed at the surface in the 9-5/8" casing. All spaces between the plugs will be filled with mud laden fluids. A steel marker will be installed as per NMOCC specifications.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Area Supt.

DATE 11-3-66

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side