

UNITED STATES
DEPARTMENT OF THE INTERIORSUBMIT IN TRIPLICATE*
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.

GEOLOGICAL SURVEY OF U. S. C.

5. LEASE DESIGNATION AND SERIAL NO.

NM 033910

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill on, to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT-1" for such proposals.)

6. IF INDIAN, ALLOTTEE OR THIRE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

McGrail Federal

9. WELL NO.

4

10. FIELD AND POOL, OR WILDCAT

Allison-Penn

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 20-8S-37E

12. COUNTY OR PARISH 13. STATE

Roosevelt

New Mexico

1. OIL WELL ☒ GAS WELL ☐ OTHER

2. NAME OF OPERATOR

Marathon Oil Company

3. ADDRESS OF OPERATOR

P. O. Box 220, Hobbs, New Mexico

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1980' FSL & 660' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

DF 4051'

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐
☐
☐
☐

PULL OR ALTER CASING

☐
☐
☐
☐

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☐
☐
☐

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

☐
☐
☒


(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Set a 40 sack cement plug at TD 9532' to cover all perforations. Cut 5-1/2" casing off at 6000'. Placed a 20 sack cement plug in and out of 5-1/2" cut off casing. A 30 sack cement plug was placed at the base of the San Andres zone. A 40 sack cement plug was placed across the 9-5/8" casing shoe at 4227'. A 10 sack cement plug was placed in the 9-5/8" casing at the surface. The hole was filled with mud. A steel marker was installed per NMOC specifications. Well plugged and abandoned 11-19-66.

18. I hereby certify that the foregoing is true and correct

SIGNED



TITLE

Acting
Area Supt.

DATE 12-13-66

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

APPROVED

DATE

MAR 2 1967

*See Instructions on Reverse Side
L. GORDON
ACTING DISTRICT ENGINEER