TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL (Other)

UNITED STATES SUBMIT IN TRIP ICATE. DEPARTM .T OF THE INTERIOR (Other Instructive verse side)

on re-

Form approved.

	Budget	Bure	au	No.	42-R	142
. LEASE	DESIGN	ATION	AN	D 8	GRIAL	NO.
NM	0339	910				

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND	REPORTS ON WELLS	
o not use this form for proposals to drill or to	deepen oriphig back to a differen	t rese

GEOLOGICAL SURVEY

	O. Box 220, Hobbs, New Mexico ocation clearly and in accordance with any State requirements.*	10. FIELD AND POOL, OR WILDCAY Allison-Penn
	1980' FSL & 660' FWL	11. SEC. T. B., M., OR BLK. AND SURVEY OR AREA Sec. 20-8S-37E
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 4051 DF	12. COUNTY OR PARISH 13. STATE ROOSevelt New Mex

NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF?

		(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)
CHANGE PLANS		(Other)
ABANDON*	<u>x</u>	SHOOTING OR ACIDIZING ABANDONMENT
MULTIPLE COMPLETE		FRACTURE TREATMENT ALTERING CASING
PULL OR ALTER CASING		WATER SHUT-OFF REPAIRING WELL,

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

We propose to plug and abandon this well per instructions and approved methods of the United States Geological Survey commencing November 2, 1966.

The proposed plugging procedure is as follows:

TD 9532'. A cement retainer at 8400'. Squeeze with 15 sacks cement beneath retainer and leave 10 sack cap on top of retainer, cut off 5-1/2" casing at approximately 8000', place a 20 sack cement plug in and out of the cut off 5-1/2" casing and a 30 sack cement plug at the top of the Tubb zone, a 30 sack cement plug at the top of the Clorietta zone, a 30 sack cement plug at the base of the San Andres zone, and a 40 sack cement plug across the 9-5/8" casing shoe at 4227. A 20 sack cement plug will be placed in the top of the 9-5/8" casing. All spaces between the plugs will be filled with mud laden fluids. A steel marker will be installed as per NMOCC specifications.

18. I hereby certify that the foregoing is true and correct Petr. Engineer TITLE (This space for Federal or State office use) 12 F APPROVED BY TITLE DATE CONDITIONS OF APPROVAL, IF ANY: Pough Specific Specification

*See Instructions on Reverse Side