



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe

Lease No. 704-071122

Unit 1

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Well No. 1 is located 650 ft. from [N] line and 650 ft. from [E] line of sec. 17
1/4 Sec. and Sec. No. 17 Twp. 13-1 Range 13-1 Meridian 13-1
Santa Fe (Field) Bernalillo (County or Subdivision) New Mexico (State or Territory)

The elevation of the derrick floor above sea level is 7000.0 ft. Mexican Federal

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

TL 1150'. lower portion of hole abandoned in April, 1962, as follows. (1150' of 11.0-4" csg. orig. set at 1150' w/500 ex cement) set 4" cement retainer at 1000' and squeezed all of bough C ports. w/30 ex cement. Mudded up hole w/100 mud iron pit. Dan McCullough, free point indicator, found 4" csg. free at 1000'; cut pipe and pulled 4" csg. set cem. plug 1000-1050 to permanently abandon lower section. Permission to permanently abandon lower sec. and temp. abandon upper sec. received from Mr. E.W. Standley 5-27-62. We now propose to abandon permanently the upper portion of hole as follows. etc. to pull 1000' of 7-3/8" 20.400 csg. set at 4710', cem. w/30 ex. will set 100' cement plug from surface to 100'; 100' cem. plug 1550-1650; install proper v.s.s.s. marker in 13-3/8" (455.45' 13-1/8" csg., 300 10-40 set at 445.45 w/370 ex csg. next, 42gel, 30 Cal-Chlor.) Location to be cleaned up by removing junk, etc., to be made ready for inspection.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Roden Oil Company

Address Box 767

Alamogordo, N.M.

By [Signature]

Title Agent

NOTIFICATION:

Subject to cement pile from 400 to 500 feet and notify this office prior to commencement of the work so it can be witnessed by the E.S.I.S.