

## SUNDRY NOTICES AND REPORTS ON WELLS

	25	<b>2∞S</b> (Twp.)	(Panga)	(Meridian)	
'ell No.		0 0	36-6	NMPM (Meridian)	
	is locat	ed <b>1980</b> ft. f	rom $\left\{ \begin{matrix} N \\ S \end{matrix} \right\}$ line an	d $\frac{660}{100}$ ft. from $\begin{bmatrix} E \\ B \end{bmatrix}$ li	ne of sec. 25
	(INDICA	TE ABOVE BY CHECK N		RT, NOTICE, OR OTHER DATA)	, 19.
OTICE OF INTE	NTION TO RE-DRILL ( INTION TO SHOOT OR INTION TO PULL OR A INTION TO ABANDON	ACIDIZE L rER CASING	SUBSEQUENT SUPPLEMENT	REPORT OF ABANDONMENT	
NOTICE OF INTE	NTION TO CHANGE PL NTION TO TEST WATE	R SHUT-OFF	SUBSEQUENT	REPORT OF SHOOTING OR ACIDI REPORT OF ALTERING CASING REPORT OF RE-DRILLING OR REF	
	NTION TO DRILL	······································	SUBSEQUENT	REPORT OF WATER SHUT-OFF	

## DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

## PLUGGING PROCEDURE:

Spot 35 sk cement plug through and above perforations  $4822-4976^{\circ}$ . Cut off  $4-\frac{1}{2}$ " casing @ 4100' and pull. Spot 50 sk cement plug @ casing stub and base of intermediate (8-5/3") casing @ 4020'. Spot 10 sk plug @ surface, install dry hole marker, clean up location for inspection.

\* Oral approval received this date.

ompany	COASTAL STATES GAS PRODUCING	Company
• •	P. O. Box 385	
	Abilene, Texas	By
		Title Production Engineer