

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM - 02919

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal-Selman

9. WELL NO.

Cne

10. FIELD AND POOL, OR WILDCAT

Bluff Penn.

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 34; T3S, 36E NM PM.

12. COUNTY OR PARISH

Roosevelt

13. STATE

N.M.

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐ Final Report of Plugging and Abandonment

2. NAME OF OPERATOR

Brace Burn Petroleum Corporation

3. ADDRESS OF OPERATOR

c/o Oliver & West, Inc., 711 N. Erway, Dallas, Texas

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.)
At surface

660' from E line; 660' from E line of Sec. 34

14. PERMIT NO.

Unknown

15. ELEVATIONS (Show whether DF, RT, OR, etc.)

6073 FB

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Propose to plug and abandon well; approved 6-15-65. Plugged and abandoned 6-28-65.

Pulled 4040' 5-1/2" casing, 1231' 13-5/8" casing.

Plugged as follows:

100' cement plug w/20 sacks cement from 9500' to 4700'

100' cement plug w/35 sacks cement from 4000' to 4100'

100' cement plug w/35 sacks cement from 1180' to 1230'

100' cement plug w/40 sacks cement from 340' to 440'

50' cement plug w/20 sacks cement on top 13-3/8" surface

Marker placed in surface casing.

18. I hereby certify that the foregoing is true and correct

SIGNED

C. A. Fuqua

TITLE

Agent

DATE

7-13-65

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

DATE