

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back into a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐

2. NAME OF OPERATOR

Breck Operating Corp.

3. ADDRESS OF OPERATOR

P.O. Box 911, Breckenridge, Texas 76024

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: Unit Letter F, 1980' FN&WL

AT TOP PROD. INTERVAL: Same

AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☒

5. LEASE

Bate Federal

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Bate Federal

9. WELL NO.

#2

10. FIELD OR WILDCAT NAME

S. Prairie / Cisco

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

22-T-8-5 R-36

12. COUNTY OR PARISH

Roosevelt

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
4094DF

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

1. Called BLM in Roswell, New Mexico, 7-15-85
2. R.I.H. with tubing, tag C.I.B.P. @ 4710'. 7-15-85
3. Mix mud using 25# salt gel per barrel of salt gel, circulate hole with mud. 7-16-85
4. Mix and spot 5 sacks of cement on C.I.B.P. 7-16-85
5. Cut casing at 4157'. P.O.H. with casing. 7-18-85
6. Spot 55 sack plug at 4210'. W.O.C. and tag top of plug @ 3920'. 7-22-85
7. Spot a 35 sack plug 2857' - 2675. 7-23-85
8. Perforate casing at 341', squeeze perforations with 70 sacks. W.O.C. 7-23-85
9. Tag plug at 210' in 7 5/8". Pressure tested 7 5/8 X 10 3/4 annulus, would not hold pressure. 7-24-85
10. Cement 7 5/8 X 10 3/4 annulus with 50 sacks. W.O.C. and test to 1000 P.S.I. Cut off wellhead, placed dry hole marker.

Note: All plugs were displaced with mud.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Samuel W. Wilson

TITLE Petroleum Engineer DATE 8/22/85

APPROVED BY  
CONDITIONS OF APPROVAL, IF ANY  
APR 25 1986

BUREAU OF LAND MANAGEMENT  
ROSWELL RESOURCE AREA

See Instructions on Reverse Side