

COUNTY	ROOSEVELT	FIELD	Wildcat	STATE	N.M.	OWWO
WC OPR	BTA OIL PRODUCERS	MAP				
1 State Ltd.						
Sec. 16, T-8-S, R-37-E						
1980' fr N Line & 660' fr W Line of Sec.						
Re-Spud 5-27-64						
P & A 6-29-64						
CLASS <i>OWN P 40422</i>						
		FORMATION	DATUM	FORMATION	DATUM	
CSG & SX - TUBING						
13 3/8"	347'	400				
9 5/8"	4140'	2000				
5 1/2"	9561'	350 (Pulled)				
5 1/2"	liner 4052-5006'	/				
		200				
LOGS	EL	GR	RA	IND	HC	A
TD 12595'						

PLUGGED & ABANDONED

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. PROP DEPTH PB 5000' TYPE
DATE

F.R. 5-28-64; OWWO, OTD 12595'
Orig. Shell Oil Co., #2 State BUA, P&A 4-21-61.
Elev. 4042' Df, Orig.
PD 5000' - SA

6-1-64 TD 12595', CO to 5016', prep to drill plug.
Pulled Old 5 1/2" casing & Ran 5 1/2" liner.

6-8-64 TD 12595', CO to 5006', testing.
Perf 4917-30' W/2 SPF
Ac. 1000 gals.

6-15-64 TD 12595', PBD 4830', swbg.
Swbd 100% wtr from 4917-30'; squeezed perfs 4917-30'
DO to 4830'
Perf @ 4750', 4756', 4757', 4759', 4767', 4773',
4778', 4780' & 4788' W/1 SPI
Swbd dry, natural.
Ac. 2000 gals.
Frac 5000 gals gelled acid + 5000# sd.

- 6-22-64 TD 12595', PBD 4710', swbg.
Did not rec load from perfs 4750-88',
Swbd 100% water
Squeezed perfs 4750-88' W/300 sx.
Perf @ 4653', 4666', 4667', 4670', 4671',
4672', 4673', 4675', 4684', 4686', 4687',
4688', 4696', & 4698' W/1 SPI
Ac. 2000 gals.
- 6-29-64 TD 12595', PBD 4710', PLUGGED & ABANDONED.
Frac 5000 gals. gelled acid + 5000# sd.
4653-98'
Swbd 100% wtr.