

HISTORY OF OIL OR GAS W L

16-43094-2 U. S. GOVERNMENT PRINTING OFFICE

It is of the greatest importance to have a complete history of the well. Please state in detail the dates of redrilling, together with the reasons for the work and its results. If there were any changes made in the casing, state fully, and if any casing was "sidetracked" or left in the well, give its size and location. If the well has been dynamited, give date, size, position, and number of shots. If plugs or bridges were put in to test for water, state kind of material used, position, and results of pumping or bailing.

Shutted 8:30 PM, MST, 6-18-57. Drilled 11" hole to 335'. Cemented 5 5/8" casing @ 332'. Circulated cement. Drilled 7 7/8" hole to 2486'. Cut Core # 1 w/ 7 3/4" core head 2486' - 2520'. Reamed and drilled 7 7/8" hole to 2590'. Cut Core # 2 w/ 7 3/4" core head 2590' - 2645'. Reamed and drilled 7 7/8" hole to 4480'. Cut Core # 3 4480' - 4537' and Core # 4 4537' - 4594' w/ 7 3/4" core head. Ran DST # 1: 4450' - 4594'. Cut Core # 5 4594' - 4651' and Core # 6 4651' - 4703'. Ran DST # 2: 4570' - 4703'. Ran DST # 3: straddle test 4481' - 4561'. Shot 50 ex. cement 4450', 25 ex. cement plug @ 2200' and 35 ex. cement @ 375'. Erected 4" x 4" marker. P & A 7-11-57.

Details of DST's and Cores given in Sundry Notices and Reports of Wells.