

ATTACHMENT - Form 9-330
Shell Oil Company, Inc.
W.P. Saunders No. 1

From	To	Total Feet	Formation						
			Sand	Shale	Chert	Anhydrite	Limestone	Dolo.	Iron Quar
4560	4620	60					60%	40%	
4620	4640	20		10%		5%		85%	
4640	4680	40		80%		10%		10%	
4680	4840	160					65%	35%	
4840	4900	60		5%			15%	80%	
4900	4950	50				65%		35%	
4950	4970	20		40%		15%	15%	30%	
4970	5130	160		95%			5%		
5130	5160	30		35%		5%	55%	5%	
5160	5220	60		40%		10%	50%		
5220	5330	110		30%		10%		60%	
5330	5430	100		60%		35%	5%		
5430	5630	200		70%		30%			
5630	5880	250		55%		15%		30%	
5880	6040	160		60%		30%		10%	
6040	6320	280		50%		20%		30%	
6320	6460	140		75%		25%			
6460	6970	510		30%		10%		60%	
6970	7010	40	5%	55%		25%		15%	
7010	7140	130		100%					
7140	7170	30		75%		15%		10%	
7170	7260	90		100%					
7260	7510	250		90%				10%	
7510	7600	90		75%				25%	
7600	7620	20	5%	65%				30%	
7620	7650	30		65%				35%	
7650	7850	200		15%				85%	
7850	8020	170			5%			95%	
8020	8070	50					40%	60%	
8070	8110	40					100%		
8110	8150	40			5%		95%		
8150	8230	80					100%		
8230	8640	410		40%			60%		
8640	8660	20		55%			20%		25%
8660	8679	19							100%

Attached are copies of all logs run in well.

On December 31, 1948, well No. 1 Saunders was plugged with 41 sack plug 3985 to 3885 feet and 10 sack plug in 8 5/8-inch casing at surface.

