

(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office Las Cruces  
Lease No. 061341  
Unit \_\_\_\_\_

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	X	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

October 4, 1948

Well No. 1-Saunders is located 1980 ft. from N line and 660 ft. from E line of sec. 5

SE/4 Sec. 5 8-S 37-E NMPM  
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)  
Bluitt Roosevelt New Mexico  
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 4072 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

T.D. 3958 feet dolomite. Ram 3920 feet 8 5/8-inch OD, casing to 3936 feet and cemented to surface with 2850 sacks. Plug down 9:57 P.M. 10-2-48. Circulated out estimated 500 sacks. Left 568 feet (177 sacks) inside casing. After W.O.C. 48 hours, will test casing with 1000 p.s.i. for 30 minutes, drill out and test cement job.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Shell Oil Company, Incorporated

Address Box 1457 Hobbs, New Mexico

By Frank R. Lovering  
Title District Superintendent