

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Las Cruces
Lease No. 061341
Unit _____

SUNDRY NOTICES AND REPORTS ON WELLS

| | | |
|---|---|----------|
| NOTICE OF INTENTION TO DRILL..... | SUBSEQUENT REPORT OF WATER SHUT-OFF..... | X |
| NOTICE OF INTENTION TO CHANGE PLANS..... | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING..... | |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF..... | SUBSEQUENT REPORT OF ALTERING CASING..... | |
| NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL..... | SUBSEQUENT REPORT OF REDRILLING OR REPAIR..... | |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE..... | SUBSEQUENT REPORT OF ABANDONMENT..... | |
| NOTICE OF INTENTION TO PULL OR ALTER CASING..... | SUPPLEMENTARY WELL HISTORY..... | |
| NOTICE OF INTENTION TO ABANDON WELL..... | | |

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

September 20, 1948

Well No. 1-Saunders is located 1980 ft. from N line and 660 ft. from E line of sec. 5
SE 1/4 Sec. 5 8-9 37E RMPN
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Blount Roosevelt New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 4072 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Shall well No. 1 Saunders was spudded 10:30 p.m. Sept. 16, 1948. Drilled 17-inch hole to 395 feet. Ran 13 3/8-inch casing to 385 feet and cemented with 300 sacks cement. Circulated with 260 sacks. W.O.C. 24 hours. Tested casing with 500 p.s.i. for 30 minutes. Held OK. Drilled cement plug from 350' to 395'. Tested casing shoe with 300 p.s.i. for 30 minutes. Held OK.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Shall Oil Company, Incorporated
Address Box 1457
Hobbs, New Mexico
By Frank R. Lovering
Title District Superintendent