

COUNTY	ROOSEVELT	FIELD	Undesignated	STATE	NM
OPR	BROWN, H. L., JR. & CLEM E. GEORGE				MAP
	1 Saunders "A"				
	Sec. 5, T-8-S, R-37-E				CO-ORD
	1650' FNL, 1650' FWL of Sec.				MX 10476
	Spd 11-16-65		CLASS	EL [REDACTED]	
	Cmp 3-18-66		FORMATION	DATUM	FORMATION DATUM
CSG & SX - TUBING					
8 5/8" 281'					
4 1/2" 4547' 350					
LOGS EL GR RA IND HC A					
			TD 4548', PBD 4546'		

San Andres Perfs 4404-4531' SHUT IN GAS WELL

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Verna Drlg. Co.	PROP DEPTH 4600'	TYPE
DATE		

F.R. 11-18-65
PD 4600' - SA
Contractor - Verna Drlg. Co.

11-22-65 Drlg. 4007' 1m.

11-29-65 TD 4548', PBD 4546', prep to perf.

12-6-65 TD 4548', PBD 4546', swbg.
Perf @ 4404', 4413', 4415', 4429', 4459',
4465', 4469', 4473', 4485', 4527', 4529',
4531';
Ac (4527-31') 2000 gals.
Swbd 1 BFPH (10% oil, 90% salt wtr) 4527-31'
Ac (4527-31') 5000 gals.
Swbd dry (4527-31')

12-14-65 TD 4548', PBD 4546', swbg load.
Ac (4404-85') 3000 gals.
Frac (4404-4531') 20,000 gals brine +
20,000# sd.

12-20-65 TD 4548', PBD 4546', swbg load.

1-3-66 TD 4548', PED 4546', tstg.
(no gauge on gas)
1-10-66 TD 4548', PED 4546', tstg.
1-17-66 TD 4548', PED 4546', tstg.
1-24-66 TD 4548', PED 4546', tstg on intermitter.
Flowing gas @ 100 MCF/GPD + 40 BFW in 24
hrs thru 1/64" chk., on intermitter.
2-14-66 TD 4548', PED 4546', tstg.
2-22-66 TD 4548', PED 4546', Shut In.
2-28-66 TD 4548', PED 4546', Shut In.
3-7-66 TD 4548', PED 4546', Shut In.
3-14-66 TD 4548', PED 4546', Shut In.
3-21-66 TD 4548', PED 4546', COMPLETED.
Flowed 370 MCF/GPD (4404-4531')
Shut In Gas Well.