m. m. vil bund. bummiddibn Form approved. P. O. BOX 1930 Budget Bureau No. 1004-0135 Form 3160-5 (November 1983) UNI O STATES HOBBS, NEW MENT THE INTERIOR Verse side) Expires August 31, 1985 5. LEASE DESIGNATION AND SERIAL NO. (Formerly 9-331) BUREAU OF LAND MANAGEMENT NM - 53389 6. IF INDIAN, ALLOTTEE OR TRIBE NAME SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.

Use "APPLICATION FOR PERMIT" for such proposals.) 7. UNIT AGREEMENT NAME WELL X WELL OTHER S. FARM OR LEASE NAME NAME OF OPERATOR Shearn-Federal Sabine Corporation 9. WELL NO. 3. ADDRESS OF OPERATOR LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface 79702 P. O. Box 3083, Midland, Texas 10. PIELD AND POOL, OR WILDCAT Allison-Pennsylvanian 11. SEC., T., B., M., OR BLK. AND SURVEY OR AREA 555' FNL and 1875' FEL of Section 25 Sec. 25, T8S, R36E, NMPM Svy 12. COUNTY OR PARISH | 13. STATE 15. ELEVATIONS (Show whether DF, RT, GR, etc.) 14. PERMIT NO. NM Roosevelt 4073 DF Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data 16. SUBSEQUENT EMPORT OF: NOTICE OF INTENTION TO PULL OR ALTER CASING WATER SHUT-OFF REPAIRING WELL TEST WATER SHUT-OFF FRACTURE TREATMENT ALTERING CABING MULTIPLE COMPLETE PRACTURE TREAT SHOOTING OR ACIDIZING ARANDON MENT® ABANDON' SHOOT OR ACIDIZE (Other) Re-entry REPAIR WELL CHANGE PLANS (NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) (Other) Re-entry 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and sones pertinent to this work.) 13-3/8" casing program "No change - Re-entry". 8-5/8" casing program "No change - Re-entry". 2-4-83 Drillout cmt plugs surf to 20' and 1075'. Clean off 5-1/2" casing stub at 4330'. 5-1/2" casing and latched on 5-1/2" casing stub at 4330'. L2-13-83 Circ out DV tool and cement 5-1/2" 17# K-55 casing at 4330' with 200 sx "C". (DV tool one joint above latch on assembly). TOC @ 2830'. Cleaned out 5-1/2" casing to 9688'. Re-perf Bough "C" 9630-48'. l-5-84 Acidized perfs 9360-48' w/250 gals 15%. Landed 2-7/8" tbg @ 9658'. Ran 2"x1-1/4"x24' L-7-84 BHD pump on 129 x 7/8" & 235 x 3/4" rods. Pumped 14 BOPD + 121 BWPD. 1-2-84 Pennsylvanian - 9557' Yates - 2847' Bough "C" - 9627' San Andres - 4080' Abo - 7737' Wolfcamp - 8923'

18. 1 bereby certify that the foresping is true and correct

SIGNED Monthson TITLE Drilling Engineer

(This space for Federal or State office use)

APPROVED BY TITLE DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

BUREAU OF LAND MANAGEMENT ROSWELL RESOURCE AREA