

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-041-00298
5. Indicate Type of Lease STATE ☒ FEE ☐
6. State Oil & Gas Lease No. V-2096

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL ☒ GAS WELL ☐ OTHER ☐	7. Lease Name or Unit Agreement Name FOX "C" STATE
2. Name of Operator LAYTON ENTERPRISES, INC.	8. Well No. 2
3. Address of Operator 3103 79TH ST. LUBBOCK, TX. 79423	9. Pool name or Wildcat ALLISON PENN
4. Well Location Unit Letter B : 660 Feet From The NORTH Line and 1480 Feet From The EAST Line Section 36 Township 8S Range 36E NMPM ROOSEVELT County	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 7065 GL	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK ☐	REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐	ALTERING CASING ☐
PULL OR ALTER CASING ☐	COMMENCE DRILLING OPNS. ☐
OTHER: ☐	PLUG AND ABANDONMENT ☒
	CASING TEST AND CEMENT JOB ☐
	OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

REMOVED MARKER & INSTALLED WELL HEADS & BOP. DRILLED CEMENT PLUGS & HEAVY MUD PLUS LARGE AMOUNT OF JUNK IN 8 5/8" CASING TO 4000' - TESTED CASING TO 500 PSI - DRILLED CEMENT PLUG TO 4 1/2" STUB @ 4192' - UNABLE TO GET THROUGH 4 1/2" CASING DUE TO JUNK & DAMAGED CASING - HOLE LOADED WITH HEAVY MUD - RAN 2 1/8" TUBING - HALLIBURTON SPOTTED 75 SK CLASS C PLUG 4229-3980 (8 5/8" SHOE @ 4164), 70 SK PLUG @ 427-295 (13 3/8" OSG. SHOE @ 381' - 13 3/8" & 8 5/8" BOTH CIRCULATED CEMENT ON ORIGINAL COMPLETION) SPOTTED 10 SK 30' - SURFACE - RE-SET MARKER & LEVEL LOCATION. WELL P & A ON 10-7-92

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Donald R. Layton TITLE PRESIDENT DATE 10-12-92
TYPE OR PRINT NAME DONALD R. LAYTON TELEPHONE NO. 800/795-8638

(This space for State Use)

APPROVED BY Jack Griffin TITLE OIL & GAS INSPECTOR DATE AN 08 1993
CONDITIONS OF APPROVAL, IF ANY: 300 HOBBS OFFICE