



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYLand Office Las Cruces
Lease No. LC 062178
Unit 8

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....		SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....		SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....		SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....		SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

February 28, 19 62

N. M. Federal #P

Well No. 3 is located 1980 ft. from N line and 660 ft. from W line of sec. 13N 1/4 Section 13

(1/4 Sec. and Sec. No.)

T6S

(Twp.)

R34E

(Range)

NMPN

(Meridian)

Wilkesand Penn

(Field)

Roosevelt

(County or Subdivision)

New Mexico

(State or Territory)

The elevation of the derrick floor above sea level is 4268 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

1. This well has been plugged and abandoned with 13 3/8" set @ 322' with cement circulated and 8 5/8" casing set @ 4006' with cement circulated. Cement plugs were placed as follows: 10 sz in top of 8 5/8", 30 sz plug from 3919 to 4006', 20 sz plug 7235 to 7300'.
2. We propose to clean out the well to approximately 4700' to complete in the San Andres. Plan to run 4 1/2" 9.5# J-55 casing and cement w/200 sz cement.
3. Propose to run G-R Correlation log and perf 4555-65', 4580-4610', 4618-28', 4637-40', and 4658-63'.
4. Acidize with 2000 gals of HCl acid and balls down 2" tubing.
5. Free down 5 1/2" casing with 20,000 gals of refined oil with 1/2 to 1# sand/ and balls gal.
6. Reverse sand and grab until flowing if necessary.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Sunray Mid-Continent Oil CompanyAddress P. O. Box 128Hobbs, New MexicoBy R. E. Statton
Title District Engineer