
Form 9-331 a (Feb. 1951)



## (SUBMIT IN TRIPLICATE)

## UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

Land Office	Les	Cruses	
Lease No.	062	L78	
Unit			

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF.
OTICE OF INTENTION TO CHANGE PLANS	s	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
OTICE OF INTENTION TO TEST WATER S	SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
IOTICE OF INTENTION TO RE-DRILL OR I	REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.
IOTICE OF INTENTION TO SHOOT OR ACI	IDIZE	SUBSEQUENT REPORT OF ABANDONMENT
OTICE OF INTENTION TO PULL OR ALTE		SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WEL	L,	-
(INDICATE AI	BOVE BY CHECK MARK NAT	TURE OF REPORT, NOTICE, OR OTHER DATA)
ell No. 4 is located	,	$\left\{\begin{array}{c} \mathbf{N} \\ \mathbf{S} \end{array}\right\}$ line and
of NE/4 Sec. 13 (14 Sec. and Sec. No.)	(Twp.) (Ran	
ssand (San Andres)	Roosevelt	N ew Mexico
(Field)	(County or Sul	bdivision) (State or Territory)
te names of and expected depths to obje	ective sands; show sizes, w ing points, and all other	OF WORK reights, and lengths of proposed casings; indicate mudding jobs, cimportant proposed work)
Drilled 7 7/8" hole in Comented in 1/2" casing 1500% for 30 mins. On Perforated 1552-56, in Ran packers and broke Attempted to sand oil Acidized with 1000 ga	DETAILS ective sands; show sizes, wing points, and all other to 4670'. Ran ng at 4662 with .X. 4577-83, 4585-8 down perfs. 4 1 frac down cas al acid and fra	OF WORK reights, and lengths of proposed casings; indicate mudding jobs, comportant proposed work)  logs. 200 sx cement. #CC 2 days. Tested (19, 4592-98, 4601-04, 4609-23, 4629-36, 4611-04)
Drilled 7 7/8" hole to comented h 1/2" casin 1500 for 30 mins. O. Perforated 4552-56, h Ran packers and broke Attempted to sand oil Acidized with 1000 garefined oil and 0 926	DETAILS sective sands; show sizes, we ing points, and all other to 1670'. Ran ag at 1662 with the section of th	OF WORK reights, and lengths of proposed casings; indicate mudding job important proposed work)  logs.  200 sx cement. FCC 2 days. Tested  9, 4592-98, 4601-04, 4609-23, 4629- 577-4630 and 4552-56 with lease oil ding - sanded out.  ctured down casing with 18,000 gall tbg. to 4580. Swabbed onto product
Drilled 7 7/8" hole of Comented h 1/2" casin 1500% for 30 mins. On Perforated 4552-56, had a packers and broke Attempted to sand oil Acidized with 1000 garefined oil and () 926 mins. On the sand oil and () 926 mins.	DETAILS ective sands; show sizes, we ing points, and all other to 1670'. Ran ag at 1662 with 1677-83, 1585-8 down perfs. It frac down cast acid and frac 100" sand. Ran at receive approval in writing timent Oil Comparison.	OF WORK reights, and lengths of proposed casings; indicate mudding jobs, comportant proposed work)  logs.  200 sx cement. #CC 2 days. Tested (19, 4592-98, 4601-04, 4609-23, 4629-36, 4601-04, 4609-23, 4629-36, 4601-04, 4609-23, 4629-36, 4601-46, 4609-23, 4629-36, 4601-46, 4609-23, 4629-36, 4601-46, 4609-23, 4629-36, 4601-46, 4609-23, 4629-36, 4601-46, 4
Drilled 7 7/8" hole of Cemented & 1/2" casin 1500% for 30 mins. On Perforated & 552-56, & Ran packers and broke Attempted to sand oil Acidized with 1000 garefined oil and () 920 mins.	DETAILS ective sands; show sizes, we ing points, and all other to 1670'. Ran ag at 1662 with 1677-83, 1585-8 down perfs. It frac down cast acid and frac 100" sand. Ran at receive approval in writing timent Oil Comparison.	OF WORK reights, and lengths of proposed casings; indicate mudding jobs, comportant proposed work)  logs.  200 sx cement. #CC 2 days. Tested (19, 4592-98, 4601-04, 4609-23, 4629-36, 4601-04, 4609-23, 4629-36, 4601-04, 4609-23, 4629-36, 4601-46, 4609-23, 4629-36, 4601-46, 4609-23, 4629-36, 4601-46, 4609-23, 4629-36, 4601-46, 4609-23, 4629-36, 4601-46, 4