

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE
(Other instructions on reverse side)

Form approved,
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 062178

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL GAS WELL OTHER Water Injection Well

7. UNIT AGREEMENT NAME

Milnesand Unit

2. NAME OF OPERATOR
UNION TEXAS PETROLEUM CORPORATION

8. FARM OR LEASE NAME

3. ADDRESS OF OPERATOR
1300 Wilco Building, Midland, Texas 79701

9. WELL NO.

513

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)
At surface

10. FIELD AND POOL, OR WILDCAT

Milnesand (San Andres)

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Unit Letter "H", 1980' FNL & 660' FEL

Sec. 24, T-8-S, R-34-E

14. PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.)
4242' DF

12. COUNTY OR PARISH 13. STATE

Roosevelt New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF
FRACTURE TREAT
SHOOT OR ACIDIZE
REPAIR WELL
(Other)

PULL OR ALTER CASING
MULTIPLE COMPLETE
ABANDON*
CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF
FRACTURE TREATMENT
SHOOTING OR ACIDIZING
(Other)

REPAIRING WELL
ALTERING CASING
ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- August 2, 1978, WIH w/coil tubing and jet washed from 4516-4695'. Pulled tubing up to 4600' and closed flow back line. Acidized w/2500 gal. 15% HCL and flushed w/soda ash water. Shut well in for 30 min. Washed back to 4695' using nitrogen, while flowing well back. RD Nowsco and returned well to water injection.
- August 8, 1978, injecting at a rate of 400 BWPD @ 1225#.

RECORDED
AUG 13 1978

U S GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED *[Signature]*
(This space for Federal or State office use)

TITLE Sr. Prod. Analyst

DATE 8-14-78

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

ACCEPTED FOR RECORD

[Signature]
AUG 17 1978

*See Instructions on Reverse Side

J. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO