

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

AUG 31 1 24 PM '65

5. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. 06174
7. Unit Agreement Name
8. Farm or Lease Name "BC" State
9. Well No. 1
10. Field and Pool, or Wildcat Undes. - San Andres
12. County Roosevelt

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>
2. Name of Operator The Atlantic Refining Company
3. Address of Operator P. O. Box 1978, Roswell, New Mexico
4. Location of Well UNIT LETTER L , 1980 FEET FROM THE South LINE AND 608.5 FEET FROM THE West LINE, SECTION 31 TOWNSHIP 7S RANGE 36E NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) 4152' DF

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input checked="" type="checkbox"/> Completion

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1703.

Drilled 7-7/8" hole to 4400' TD. Ran 140 jts of 4-1/2" OD 8R 9.5# & 10.5# J-55 casing w/float collar and float shoe = 4389.98'. Set at 4399.98'. Cemented w/320 sx Incor neat. Plug down at 5:30 PM 7/29/65. Top of cement at 3400' by temperature survey. Tested 4-1/2" casing to 1000# for 30 min. OK & job complete at 1:30 PM 8/1/65 after 68 hours WOC. Perforated San Andres w/1 jet shot at 4281, 4289, 4296, 4299 & 4304' (ES). Treated w/2000 gal. of 15% acid, 20,000 gallons of lease crude containing 1/20#/gal. Adomite & 20,000# of 20/40 sand. Ran 2" tubing for completion.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *D. J. Litcher* TITLE Dist. Drilling Supervisor DATE 8-24-65

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: