

CO. NTY Roosevelt		FIELD Undesignated		STATE N.M.		NO.	
OPR. H. L. Brown, Jr. & Clem E. George				MAP			
NO. 1		LSE O. G. McClain					
SEC. 11		T. 8S		BLK. R		34E SUR.	
LOC. 660' fr S Line & 2310' fr W Line of Sec.				CO-ORD.			
MI.		FROM		CLASS.		EL. 4275' 2	
SPUD. 4-22-63		COMP. 6-19-63		FORMATION		DATUM	
TRI. 2000 Ac., SOF 20,000		LOG:					
+ 25,000# sd.		Anhy		1955			
CSG. & SX.		Yates		2585			
8 5/8" 355' 250		Queen		3400			
4 1/2" 4664' 250		SA		3790			
		SA Porosity					
TBG. DEPTH		SIZE		4540			
LOGS EL GR RA IND HC A							
		TD 4669'				PB 4635'	
PROD INT.		(DAILY RATE)		BS&W GH		GOR GTY C. P. T. P. HRS. TEST	
4583-4612'		Flo. 15 BO + 2 BW		24/64"		30. 350# 110# 24'	
(San Andres)							

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Tri-Service Drlg. Co.	PROP DEPTH 4800'	TYPE
DATE		

F.R. 4-25-63, San Andres
 PD 4800' - Tri-Service Drlg. Co., Contractor
 4-29-63 Drlg. 4303' ls. & anhy.
 5-6-63 TD 4669', prep to perf.
 Cored 4614-64', rec 50' dolo., sli. show oil through-
 out.
 5-13-63 TD 4669', flg. load. (-390 BLO).
 Perf @ 4583', 4586', 4589', 4596', 4600', 4603',
 4606', & 4612', treated 2000 gals acid,
 SOF 20,000 gals ref. oil + 25,000# sd.
 5-20-63 TD 4669', flg. load.
 Fld. 40 BLO/24' thru 30/64" ch., TP 125#, CP 50#.
 (-254 BLO).
 5-27-63 TD 4669', flg. load.
 Flg. 10-12 BLOPD + 2-3% wtr (-168 BLO).
 6-3-63 TD 4669', flg. load.
 Flg. 8-10 BLOPD (-125 BLO).
 6-10-63 TD 4669', flg. load.
 Fld. 8-10 BLOPD (-80 BLO).

H. L. Brown, Jr. & Clem E. George, #1 O. G. McClain -
Sec. 11-8S-34E

6-17-63 TD 4669', building tank batteries.
Load Recovered.

6-24-63 TD 4669', PB 4635', COMPLETED.