TYPE OR PRINT NAME GEORGE SHEFFER

CONDITIONS OF APPROVAL, IF ANY:

(This Space for State Use)

APPROVED BY

JUN - 4 1993

_ DATE __

Revised 1-1-89 Energy, Minerals and Natural Resource Department to Appropriate **District Office** OIL CONSERVATION DIVISION DISTRICT I WELL API NO. P.O. Box 1980, Hobbs, NM 88240 30-041-10017 P.O. BOX 2088 Santa Fe, New Mexico 87504-2088 5. Indicate Type of Lease DISTRICT II FEE 🛚 STATE P.O. Drawer DD, Artesia, NM 88210 6. State Oil & Gas Lease No. DISTRICT III 1000 Rio Brazos Rd., Aztec NM 87410 SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A 7, Lesse Name or Unit Agreement Name DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: Milnesand Unit OIL GAS INJECTION WELL OTHER WELL 2. Name of Operator 8. Well No. 127 MAERSK ENERGY Inc. 9. Pool name or Wildcat 3. Address of Operator 2424 Wilcrest, Suite 200, Houston, TX 77042-2753 Milnesand (San Andres) Unit Letter F: 1974.7 Feet From The North Line and 1900.5 Feet From The West Line 8S Range <u>35E</u> NMPM _ SE NW Section _____ Township _ County ____ 10. Elevation (Show whather DF, RKB, RT, GR, etc.) 4251.0' Check Appropriate Box to Indicate Nature of Notice, Report, Or Other Data SUBSEQUENT REPORT OF: NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS.

PLUG AND ABANDONMENT PULL OR ALTER CASING CASING TEST AND CEMENT JOB□ OTHER: __CLEAN-OUT, REPERFORATE & STIMULATE OTHER: 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. Work Described: Thru tubing clean-out, reperforating & stimulation of San Andres Injection Well Work Commenced: 05/18/93 05/20/93 Work Completed: Operations Detail: Cleaned-out well to 4672' with coiled tubing. 1) Spot 220 gallons of S444 Calcium Sulfate Converter Chemical. 2) Perforate San Andres with 4 SPF from: 3) 4592' - 4606' 4609' - 4611' 4620' - 4643' 4657' - 4664' 41 Acidize San Andres perfs with 2500 gallons of 15% HCL acid. Place well back in service. Thereby certify that the information aboye is true and complete to the best of my knowledge and belief. TITLE DRILLING MANAGER DATE May 28, 1993 SIGNATURE ___ TELEPHONE NO. 713/783-0376

TITLE _____