

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resource Department

Form C-103
Revised 1-1-89

DISTRICT I

P.O. Box 1980, Hobbs, NM 88240

DISTRICT II

P.O. Drawer DD, Artesia, NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec NM 87410

OIL CONSERVATION DIVISION

P.O. BOX 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.

30-041-10017 ✓

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

Milnesand Unit

8. Well No. 127

9. Pool name or Wildcat

Milnesand (San Andres)

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS.)

1. Type of Well:

OIL WELL GAS WELL ☐ OTHER INJECTION

2. Name of Operator

MAERSK ENERGY Inc.

3. Address of Operator

2424 Wilcrest, Suite 200, Houston, TX 77042-2753

4. Well Location

Unit Letter F : 1974.7 Feet From The North Line and 1900.5 Feet From The West Line
SE NW Section 7 Township 8S Range 35E NMPM _____ County Roosevelt

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

4251.0'

11. Check Appropriate Box to Indicate Nature of Notice, Report, Or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: CLEAN OUT, REPERFORATE & STIMULATE ☒

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: _____ ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. MAERSK proposes to clean-out, reperforate and acid stimulate this Milnesand (San Andres) Unit Injection Well using the following thru-tubing procedure:

- 1) Clean out well to PBD with coiled tubing.
- 2) Spot 3 BBLs of S444 converter chemicals (calcium sulfite removal).
- 3) Perforate San Andres with 4SPF using a thru tubing gun from:

4592' - 4606'
4609' - 4611'
4620' - 4643'
4657' - 4664'

- 4) Acidize well with 2500 gallons 15% HCL acid using pressure fluctuation tool on coiled tubing.
- 5) Place well back in service.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE George Sheffer TITLE DRILLING MANAGER DATE May 17, 1993

TYPE OR PRINT NAME GEORGE SHEFFER TELEPHONE NO. 713/783-0376

(This Space for State Use)

ORIGINAL SIGNED BY JERRY SEXTON

APPROVED BY DISTRICT I SUPERVISOR TITLE _____ DATE MAY 21 1993