

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE. If State Land submit 6 Copies

AREA 640 ACRES
LOCATE WELL CORRECTLY

Cactus Drilling Company State "ND"
(Company or Operator) (Lease)

Well No. 1, in SE 1/4 of SE 1/4, of Sec. 28, T. 7 N., R. 36 E., NMPM.
Wilcat Pool, Roosevelt County.

Well is 660 feet from South line and 660 feet from East line
of Section 28. If State Land the Oil and Gas Lease No. is E 9013

Drilling Commenced 3-16, 1965 Drilling was Completed 6-1, 1965.

Name of Drilling Contractor Cactus Drilling Company
Address Hobbs, New Mexico

Elevation above sea level 4128 D.F. The information given is to be kept confidential until
, 19.

OIL SANDS OR ZONES

No. 1, from to No. 4, from to
No. 2, from to No. 5, from to
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.
No. 2, from to feet.
No. 3, from to feet.
No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
8-5/8"	24#	Used	350'				Surface
4-1/2	10.5#	Used	4594	Halliburton		4468-4446	Oil String

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
11"	8-5/8	365	175	Circ		
7-7/8"	4-1/2	4606	200	Halliburton		

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Treated through perforations 4468-4446 w/1000 gal acid. Swabbed back acid and salt water w/no productivity of oil or gas indicated.

Result of Production Stimulation

Depth Cleaned Out

JORD OF DRILL-STEM AND SPECIAL TE

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 4606 TD feet, and from feet to feet.
Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to Producing Dry hole, 19

OIL WELL: The production during the first 24 hours was barrels of liquid of which was oil; % was emulsion; % water; and % was sediment. A.P.I. Gravity.

GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of liquid Hydrocarbon. Shut in Pressure lbs. Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico			Northwestern New Mexico		
T. Anhy.	2230		T. Devonian		T. Ojo Alamo
T. Salt.	2290		T. Silurian		T. Kirtland-Fruitland
B. Salt.	2420		T. Montoya		T. Farmington
T. Yates.	2500		T. Simpson		T. Pictured Cliffs
T. 7 Rivers			T. McKee		T. Menefee
T. Queen	3180		T. Ellenburger		T. Point Lookout
T. Grayburg			T. Gr. Wash		T. Mancos
T. San Andres	3637		T. Granite		T. Dakota
T. Glorieta			T.		T. Morrison
T. Drinkard			T.		T. Penn
T. Tubbs			T.		T.
T. Abo			T.		T.
T. Penn			T.		T.
T. Miss			T.		T.

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	2230	2230	Surf, r. bed				
2230	2290	60	Anhy				
2290	2420	130	Salt				
2420	2500	80	Anhy				
2500	2610	110	Sand				
2610	3637	1027	Anhy w/Salt strgrs				
3637	4606	969	Dolo & Anhy				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

June 30, 1965
Company or Operator Cactus Drilling Company Address Drawer 2068, Hobbs, New Mexico
Name Joe W. Baker Position Vice President