

COUNTY	ROOSEVELT		FIELD	Chaveroo	STATE	NM
OPR	CHAMPLIN PET. CO.				MAP	
	1 Shell-State					
	Sec. 32, T-7-S, R-33-E				CO-ORD	
	660' fr N Line & 1980' fr W Line of Sec.					
	Spd 5-11-65		CLASS		E	
	Cmp 5-23-65		FORMATION	DATUM	FORMATION	DATUM
CSG & SX - TUBING			LOG:			
			Anhy 1903			
8 5/8" 403' 300			Yates 2291			
4 1/2" 4379' 350			Queen 2977			
			SA 3533			
LOGS EL GR RA IND HC A						
			TD 4380', PBD 4374'			

IP San Andres Perfs 4305-48' Swbd 54 BOPD + 23 BW. Pot. Based on 24 hr test, gravity 24.6.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Cactus Drlg. Co.	PROP DEPTH	4500'	TYPE
DATE			

F.R. 5-6-65
PD 4500' - SA
Contractor - Cactus Drlg. Co.
5-17-65 Drlg. 4026' dolo & lm.
5-24-65 TD 4380', prep to perf.
DST 4209-4380', open 2 hrs,
rec 240' gas in DP + 243' GCM,
1 hr ISIP 1340#, FP 139-185#,
1 hr FSIP 1020#.
6-1-65 TD 4380', PBD 4374', COMPLETED.
Perf @ 4305', 4314', 4324', 4332', 4335',
4338', 4348' W/2 SPI
Ac. 2250 gals.
Frac 25,000 gals oil + 25,000# sd.

COUNTY	ROOSEVELT		FIELD	Undesignated		STATE	NM	
OPR	CHAMPLIN PETROLEUM COMPANY						MAP	
1 State								
Sec. 32, T-7-S, R-33-E						CO-ORD		
660' fr N Line & 1980' fr E Line of Sec.								
Spud 4-5-65			CLASS			E		
Comp 4-19-65			FORMATION	DATUM	FORMATION	DATUM		
CSG & SX - TUBING			LOG:					
			Anhy 1915					
			Yates 2293					
			Queen 2973					
			SA 3532					
8 5/8" 417' 300								
4 1/2" 4379' 350								
LOGS EL GR RA IND HC A								
			TD 4380'					

IP San Andres Perfs 4280-4346' Swbd 73 BOPD + 63 BW. Pot. Based on 24 hr test, gravity 24.6.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Cactus Drlg. Co. PROP DEPTH 4500' TYPE
DATE

4426
3532
1858

F.R. 4-8-65; Oper's Elev. 4420' G1
PD 4500' - SA
Contractor - Cactus Drlg. Co.
4-12-65 Drlg. 4074' lm.
4-19-65 TD 4380', prep to Acidize.
DST 4290-4380', open 2 hrs,
rec 35' SOCM + 90' DM,
1 hr ISIP 1312#, FP 57-114#,
1 hr FSIP 914#.
Perf 4280-84', 4301-04', 4309-12', 4322-28',
4333-36', 4343-46' W/2 SPF
4-26-65 TD 4380' COMPLETED.
Ac. 500 gals (MA)
Ac. 2500 gals (15%).