

COUNTY	ROOSEVELT		FIELD	Chaveroo		STATE	NM	
OPR	CHAMPLIN PETROLEUM CO.							
	1 Lauck-Federal						MAP	
	Sec. 29, T-7-S, R-33-E							
	660' fr S & E Lines of Sec.						CO-ORD	
	Spd 7-7-65							
	Cmp 7-20-65							
			CLASS				EL [REDACTED]	
CSG & SX - TUBING	LOG:	FORMATION	DATUM	FORMATION	DATUM			
		Anby 1905						
		Yates 2308						
		Queen 2980						
		SA 3542						
LOGS	EL	GR	RA	IND	HC	A		
							TD 4460', PBD 4455'	

IP San Andres Perfs 4282-4348' Flwd 165 BOPD + 18 BW. Pot.
Based on 24 hr test thru 28/64" chk., TP 80#, gravity 24.6,
GOR 386.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Sitton & Norton Drlg. Co. PROP DEPTH 4500' TYPE
DATE

F.R. 7-8-65
PD 4500' - SA
Contractor - Sitton & Norton Drlg. Co.
7-12-65 Drlg. 3575'.
7-19-65 TD 4460', WOC.
DST 4230-4460', open 1 hr 30 mins,
GTS 22 mins,
Rec 1100' HO&GCM + 40' oil & mud (50% oil, 50%
mud), 1 hr ISIP 1418#, FP 258-442#,
1 hr 30 min FSIP 1383#.
7-26-65 TD 4460', PBD 4455', COMPLETED.
Perf @ 4282', 4288', 4296', 4310', 4315',
4324', 4331', 4339', 4348' W/2 SPI
Ac. 2500 gals.