

COUNTY	ROOSEVELT		FIELD	Chaveroo	STATE	NM
OPR	CHAMPLIN PETROLEUM CO.				MAP	
	2 Lauck-Federal					
	Sec. 29, T-7-S, R-33-E				CO-ORD	
	1980' fr S Line & 660' fr E Line of Sec.					
	Spd 8-12-65				CLASS	EL [REDACTED]
	Cmp 9-3-65					
			FORMATION	DATUM	FORMATION	DATUM
CSG & SX - TUBING	LOG:	Anhy	1876			
		Yates	2310			
		Queen	2977			
		SA	3532			
		Pie Marker				
			4030			
LOGS EL GR RA IND HC A						
		TD 4440', PBD 4438'				

IP San Andres Perfs 4230-4392' Swbd 260 BOPD + 16 BW. Pot.
Based on 24 hr test, gravity 24.6.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT.	Sitton & Norton	PROP DEPTH 4500'	TYPE
DATE			

F.R. 7-22-65; Oper's Elev. 4440' KB
PD 4500' - SA
Contr. - Sitton & Norton
8-17-65 Drlg. 3125' anhy.
8-23-65 Coring @ 4352'.
Cored 4240-4299', rec 57' anhy dolo., w/bldg oil, gas & salt wtr.
8-30-65 TD 4440', WOC.
Cored 4299-4358', rec 59' anhy dolo., w/bldg oil & gas.
Cored 4358-4417', rec 59' anhy dolo., w/bldg oil & gas.
Cored 4417-40', rec 23' anhy dolo., w/sli bldg oil & gas.
DST 4204-4440', mis-run.
DST 4254-4440', open 1 hr 30 mins,
rec 220' HO&GCM + 100' GC Brackish watery DM,
w/tr. oil, CONTINUED

8-30-65 Continued
1 hr ISIP 1398#, FP 158-201#,
1 hr 30 min FSIP 1270#.
9-7-65 TD 4440', PBD 4438', flwg load.
Perf @ 4230', 4234', 4240', 4289', 4312',
4319', 4328', 4334', 4385', 4392' W/2 SPI
Ac. 2500 gals.
Swbd dry.
Frac 25,000 gals oil + 25,000# sd. 4230-4392'
9-13-65 TD 4440', PBD 4438', COMPLETED.