

COUNTY ROOSEVELT		FIELD Chaveroo		STATE NM	
OPR CHAMPLIN PETROLEUM CO.				MAP	
4 State					
Sec. 32, T-7-S, R-33-E				CO-ORD	
660' fr S & E Lines of Sec.					
Spd 7-31-65		CLASS		E	
Cmp 8-16-65					
CSG & SX . TUBING		LOG:			
		Anhy 1893			
		Yates 2328			
8 5/8" 367' 200		Queen 3000			
4 1/2" 4484' 325		SA 3567			
LOGS EL GR RA IND HC A					
		TD 4484'			

IP San Andres Perfs 4289-4372' Swbd 266 BOPD + 8 BW. Pot. Based on 24 hr test, gravity 24.6.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Sitton & Norton PROP DEPTH 4500' TYPE
DATE

F.R. 6-10-65
PD 4500' - SA
Contractor - Sitton & Norton
8-2-65 TD 367', prep to drill
8-9-65 Drlg. 4242' dolo.
8-17-65 TD 4484', prep to frac.
DST 4254-4484', open 1 hr 30 mins,
rec 442' O&GC Drlg Mud + 150' blk wtr &
GCM,
1 hr ISIP 1420#, FP 210-459#,
1 hr FSIP 1364#.
Perf @ 4289', 4296', 4306', 4310', 4316',
4320', 4333', 4342', 4346', 4359', 4366',
4372' W/2 SPF
Ac. 2500 gals. 4289-4372'.
8-23-65 TD 4484', COMPLETED.
Frac 25,000 gals oil + 25,000# sd. 4289-4372'.