

COUNTY	ROOSEVELT		FIELD	Chaveroo		STATE	NM	
OPR	CHAMPLIN PETROLEUM COMPANY					MAP		
	6 State					CO-ORD		
	Sec. 32, T-7-S, R-33-E							
	660' fr S Line & 1980' fr E Line of Sec.							
	Spd 8-27-65					CLASS		
	Cmp 9-19-65					FORMATION	DATUM	FORMATION
CSG & SX - TUBING	LOG:					Anhy	1842	
						Yates	2342	
						Queen	3012	
						SA	3575	
LOGS EL GR RA IND HC A								
						TD 4480'	PBD 4472'	

IP San Andres Perfs 4227-4449' Swbd 204 BOPD, + 54 BW. Pot.
Based on 24 hr test, gravity 24.6.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT.	Sitton & Norton	PROP DEPTH	4500'	TYPE
DATE				

F.R. 8-12-65
PD 4500' - SA
Contr. - Sitton & Norton
8-30-65 Drlg. 2925'.
9-7-65 TD 4362', prep to core.
Cored 4245-4303', rec 57' dolo & anhy., w/very
scatt shows.
Cored 4303-62', rec 59' dolo., w/scatt shows.
9-13-65 TD 4480', WOC.
Cored 4362-4421', rec 59' anhy dolo., w/NS.
Cored 4421-80', rec 59' dolo., w/scatt shows.
DST 4211-4480', open 1 hr 30 mins,
rec 325' sli GCM, w/sui odor,
1 hr ISIP 1414#, FP 155-353#,
1 hr 30 min FSIP 1366#.

20-65 TD 4480', PBD 4472', swbg load.
Perf @ 4227', 4232', 4244', 4262', 4270',
4304', 4316', 4326', 4336', 4349', 4372',
4385', 4440', 4449' W/2 SPI
Ac. 3500 gals.,
Frac 25,000 gals oil + 25,000# sd.
9-27-65 TD 4480', PBD 4472', COMPLETED.